

2017–2021





2020–2022

Limitations on Uncloneable Encryption and Simultaneous One-Way-to-Hiding

Christian Majenz[1,2,4], Christian Schaffner[2,3], Mehrdad Tahmasbi[2,3]

[1] Centrum Wiskunde & Informatica (CWI), Amsterdam, Netherlands
[2] QuSoft, Amsterdam, Netherlands
[3] Institute for Logic, Language and Computation (ILLC), University of Amsterdam, Amsterdam, Netherlands
[4] Department of Applied Mathematics and Computer Science, Technical University of Denmark, Kgs. Lyngby, Denmark

christian.majenz@cwi.nl, c.schaffner@uva.nl, m.tahmasbi@uva.nl

arXiv:2103.14510v3 [quant-ph] 4 Nov 2021

Abstract. We study uncloneable quantum encryption schemes for classical messages as recently proposed by Broadbent and Lord [BL20]. We focus on the information-theoretic setting and give several limitations on the structure and security of these schemes: Concretely, 1) We give an explicit cloning-indistinguishable attack that succeeds with probability $\frac{1}{2} + \mu/16$ where μ is related to the largest eigenvalue of the resulting quantum ciphertexts. 2) For a uniform message distribution, we partially characterize the scheme with the minimal success probability for cloning attacks. 3) Under natural symmetry conditions, we prove that the rank of the ciphertext density operators has to grow at least logarithmically in the number of messages to ensure uncloneable security. 4) The *simultaneous* one-way-to-hiding (O2H) lemma is an important technique in recent works on uncloneable encryption and quantum copy protection. We give an explicit example which shatters the hope of reducing the multiplicative "security loss" constant in this lemma to below 9/8.

1 Introduction

The linearity of quantum mechanics, leading to features like the "quantum no-cloning theorem" and the imperfect distinguishability of non-orthogonal quantum states, has opened up several opportunities in cryptography. In fact, the very first protocols in quantum information processing where cryptographic applications capitalizing on the mentioned features of quantum theory, like Wiesner's quantum money [Wie83] and the BB84 key exchange protocol [BB84] (for a survey of other cryptographic applications, see [BS16]). Another application of the fact that quantum information cannot be copied, called *uncloneable encryption*, was recently explored by Broadbent and Lord [BL20]: Using a secret key, Alice encrypts a classical message into a *quantum* ciphertext, which is passed to a cloner, Eve, who copies the ciphertext into two quantum registers. These quantum registers are then provided to two separated parties, Bob and Charlie. Alice also provides the secret key to Bob and Charlie who attempt to guess the message. The adversaries Eve, Bob, and Charlie win if and only if Bob and Charlie both correctly decrypt the message. Given a message drawn from some (possibly adversarially chosen) distribution p over a set of size M, the adversaries can always win with the maximum probability that p assigns to any message, by outputting the same fixed message as their guess. The goal is to devise an encryption scheme such that 1) a legitimate receiver can recover the message from the ciphertext and the secret key; 2) the probability that the adversaries win does not significantly exceed the trivial success probability. Following [BL20], we call the latter requirement *uncloneable-security*, which is a strengthening of the confidentiality notion using the same message distribution (e.g. one-wayness if p is the uniform distribution, and IND if p is uniform on an adversarially chosen pair of messages).[5] Studying this notion of security is motivated by cryptographic applications such as quantum money and the prevention of storage attack by classical adversaries[6] [BL20]. Furthermore, uncloneable encryption is fundamentally related to quantum copy-protection [Aar09,ALL+20,ALP20,CMP20].

[5] Gottesman studied a different definition of uncloneable encryption called *quantum tamper-detection* [Got03].

[6] In this scenario, an eavesdropper Eve without quantum memory is forced to immediately measure any intercepted quantum ciphertexts, without knowing the key (yet). Uncloneable security implies that these classical measurement outcomes cannot be used to determine the message even after learning the key, because otherwise, copying these classical outcomes and handing them to Bob and Charlie would violate uncloneable security.

