

2021 2023

Structural risk minimization for quantum linear classifiers

Casper Gyurik[1], Dyon van Vreumingen[1,2,3], and Vedran Dunjko[1,4]

[1]LIACS, Leiden University, Niels Bohrweg 1, 2333 CA Leiden, Netherlands
[2]QuSoft, Centrum Wiskunde & Informatica (CWI), Science Park 123, 1098 XG Amsterdam, Netherlands
[3]Institute of Physics, University of Amsterdam, Science Park 904, 1098 XH Amsterdam, the Netherlands
[4]LION, Leiden University, Niels Bohrweg 2, 2333 CA Leiden, Netherlands

December 4th, 2022

arXiv:2105.05566v3 [quant-ph] 10 Jan 2023

Quantum machine learning (QML) models based on parameterized quantum circuits are often highlighted as candidates for quantum computing's near-term "killer application". However, the understanding of the empirical and generalization performance of these models is still in its infancy. In this paper we study how to balance between training accuracy and generalization performance (also called structural risk minimization) for two prominent QML models introduced by Havlíček et al. [1], and Schuld and Killoran [2]. Firstly, using relationships to well understood classical models, we prove that two model parameters – i.e., the dimension of the sum of the images and the Frobenius norm of the observables used by the model – closely control the models' complexity and therefore its generalization performance. Secondly, using ideas inspired by process tomography, we prove that these model parameters also closely control the models' ability to capture correlations in sets of training examples. In summary, our results give rise to new options for structural risk minimization for QML models.

1 Introduction

After years of efforts the first proof-of-principle quantum computations that arguably surpass what is feasible with classical supercomputers have been realized [3]. As the leap from noisy intermediate-scale quantum (NISQ) devices [4] to full-blown quantum computers may require further decades, finding practically useful NISQ-suitable algorithms is becoming increasingly important. It has been argued that some of the most promising NISQ-suitable algorithms are those that rely on *parameterized quantum circuits* (also called variational quantum circuits) [5, 6]. Such algorithms have been proposed for quantum chemistry [7, 8], for optimization [9], and for machine learning [10]. One of the advantages of parameterized quantum circuits is that restrictions of NISQ devices can be hardwired into the circuit. Moreover, families of parameterized quantum circuits can – under widely believed complexity-theoretic assumptions – realize input-output correlations that are intractable for classical computation [11, 12]. In this paper we discuss the application of parameterized quantum circuits as machine learning models in hybrid quantum-classical methods. The use of NISQ devices in the context of machine learning is particularly appealing as machine learning algorithms may be more tolerant to noise in the quantum hardware [13, 14]. In short, parameterized quantum circuits could yield NISQ-friendly machine learning models that could be used to classify data for which conventional classical machine learning models may struggle.

In machine learning, parameterized quantum circuits can serve as a parameterized family of real-valued functions in a manner similar to neural networks (they are often called quantum neural networks). It has been noted that machine learning models based on parameterized quantum circuit are closely related to *linear classifiers*, which use hyperplanes to separate classes of data embedded in a vector space. This connection was first established by Havlíček et al. [1], and Schuld & Killoran [2], who both defined two machine learning models based on parameterized quantum circuits that efficiently implement certain families of linear classifiers – an illustration of which can be found in Figure 1. In

Casper Gyurik: c.f.s.gyurik@liacs.leidenuniv.nl

