






Solving correlation clustering with QAOA and a Rydberg qudit system: a full-stack approach

Jordi R. Weggemans[1,2], Alexander Urech[3,2], Alexander Rausch[4], Robert Spreeuw[3,2], Richard Boucherie[5], Florian Schreck[3,2], Kareljan Schoutens[6,2], Jiří Minář[6,2], and Florian Speelman[7,2]

[1]CWI, Science Park 123, 1098 XG Amsterdam, The Netherlands
[2]QuSoft, Science Park 123, 1098 XG Amsterdam, The Netherlands
[3]Van der Waals-Zeeman Institute, Institute of Physics, University of Amsterdam, Science Park 904, 1098 XH Amsterdam, the Netherlands
[4]Robert Bosch GmbH, Corporate Research, Robert-Bosch-Campus 1, 71272 Renningen, Germany
[5]Stochastic Operations Research, Department of Applied Mathematics, University of Twente, 7500 AE, Enschede, The Netherlands.
[6]Institute for Theoretical Physics, University of Amsterdam, Science Park 904, 1098 XH Amsterdam, the Netherlands
[7]Informatics Institute, University of Amsterdam, Science Park 904, 1098 XH Amsterdam, the Netherlands

arXiv:2106.11672v3 [quant-ph] 25 Mar 2022

We study the correlation clustering problem using the quantum approximate optimization algorithm (QAOA) and qudits, which constitute a natural platform for such non-binary problems. Specifically, we consider a neutral atom quantum computer and propose a full stack approach for correlation clustering, including Hamiltonian formulation of the algorithm, analysis of its performance, identification of a suitable level structure for ^{87}Sr and specific gate design. We show the qudit implementation is superior to the qubit encoding as quantified by the gate count. For single layer QAOA, we also prove (conjecture) a lower bound of 0.6367 (0.6699) for the approximation ratio on 3-regular graphs. Our numerical studies evaluate the algorithm's performance by considering complete and Erdős-Rényi graphs of up to 7 vertices and clusters. We find that in all cases the QAOA surpasses the Swamy bound 0.7666 for the approximation ratio for QAOA depths $p \geq 2$. Finally, by analysing the effect of errors when solving complete graphs we find that their inclusion severely limits the algorithm's performance.

1 Introduction

The Quantum Approximate Optimization Algorithm (QAOA) is a promising attempt at trying to find a quantum advantage when using near-term Noisy Intermediate-Scale Quantum (NISQ) devices [50]. The current body of literature points into mixed directions as far as the utility of QAOA is concerned: whilst it has provable advantages such as recovering near optimal query complexity in Grover's search [74], exhibiting universality [86, 92] and the possibility for quantum supremacy [49], there are also known limitations in the low depth regime [7, 26, 65, 90]. However, current analytical tool for analysing the performance of QAOA have only been able to investigate very specific problem instances, predominantly at low depth [32, 52, 145, 146, 150]. A general analytical approach remains to be found, which is why a large portion of the literature resorts to numerical simulation.

Earlier work on QAOA studied problems such as MAXCUT [50, 62, 145] and MAX E3LIN2 [51], where the translation procedure entails translating constraints on a binary string into a cost Hamiltonian. In the current work we focus on the *correlation clustering* problem. First introduced by Bansal et al. [16], reductions to correlation clustering are common in machine-learning contexts, with applications ranging from data analysis [21] to image recognition and pose estimation [71]. Since it is a computationally intensive task to find these clusterings, with approxima-

