
2017–2021






2020–2022

Local simultaneous state discrimination

Christian Majenz[*1], Maris Ozols[†2], Christian Schaffner[‡3], and Mehrdad Tahmasbi[§4]

[1] *Department of Applied Mathematics and Computer Science, Technical University of Denmark*
[2] *Institute for Logic, Language, and Computation, Korteweg-de Vries Institute for Mathematics, and Institute for Theoretical Physics, University of Amsterdam and QuSoft*
[3] *Institute for Logic, Language, and Computation, University of Amsterdam and QuSoft*
[4] *Centrum Wiskunde & Informatica and QuSoft*

November 3, 2021

arXiv:2111.01209v1 [quant-ph] 1 Nov 2021

Abstract

Quantum state discrimination is one of the most fundamental problems studied in quantum information theory. Applications range from channel coding to metrology and cryptography. In this work, we introduce a new variant of this task: Local Simultaneous State Discrimination (LSSD). While previous distributed variants of the discrimination problem always allowed some communication between the parties to come up with a joint answer, the parties in LSSD cannot communicate and have to simultaneously answer correctly. This simultaneity implies, e.g., that for classical states, the problem does not trivialize to a non-distributed distinguishing task. While interesting in its own right, this problem also arises in quantum cryptography.

After introducing the problem, we give a number of characterization results. We give examples showing that i) the optimal strategy for local discrimination need not coincide with the optimal strategy for LSSD, even for classical states, ii) an additional entangled resource can increase the optimal success probability in LSSD, and iii) stronger-than-quantum non-signalling resources can allow for a higher success probability in some cases, compared to strategies using entanglement. Finally, we show that finding the optimal strategy in (classical) 3-party LSSD is NP-hard.

1 Introduction

Discriminating between a known set of quantum states is a well-studied and fundamental problem in quantum information theory, with a vast range of applications ranging from cryptography and quantum computing to quantum information and metrology [BK15]. A referee randomly picks a quantum state from a known set of states and sends it to Alice who tries to determine which state was sent to her. An interesting extension of the problem is *distributed* state discrimination where the states to be distinguished are bi-partite and Alice gets to examine register A and Bob register B. In the context of nonlocality, the most commonly considered scenario is *LOCC* where Alice and Bob are allowed to use *local operations and classical communication* in the discrimination process [CLM+14]. For example, any orthonormal set of product states can be prepared by local operations and discriminated by a global one, however discriminating them with only local operations is generally not possible, even when classical communication between parties is allowed [BDF+99, CLMO13]. In the LOCC setting, the discrimination task does not become more demanding by asking Alice and Bob to answer correctly *simultaneously* since the result can be communicated between the parties.

Surprisingly, the more restricted scenario where Alice and Bob can only use *local operations (LO)* without any classical communication has received only little attention in the published literature so far,

[*] chmaj@dtu.dk
[†] marozols@gmail.com
[‡] c.schaffner@uva.nl
[§] mehrdad@cwi.nl