

2022–2024

arXiv:2111.08045v2 [quant-ph] 22 Nov 2022

General stabilizer approach for constructing highly entangled graph states

Zahra Raissi,[1,2,3] Adam Burchardt,[4] and Edwin Barnes[1,2]

[1] *Department of Physics, Virginia Tech, Blacksburg, VA 24061, USA*
[2] *Virginia Tech Center for Quantum Information Science and Engineering, Blacksburg, VA 24061, USA*
[3] *ICFO-Institut de Ciencies Fotoniques, The Barcelona Institute of Science and Technology, Castelldefels (Barcelona), 08860, Spain*
[4] *QuSoft, CWI and University of Amsterdam, Science Park 123, 1098 XG Amsterdam, the Netherlands*

Highly entangled multipartite states such as k-uniform (k-UNI) and absolutely maximally entangled (AME) states serve as critical resources in quantum networking and other quantum information applications. However, there does not yet exist a complete classification of such states, and much remains unknown about their entanglement structure. Here, we substantially broaden the class of known k-UNI and AME states by introducing a method for explicitly constructing such states that combines classical error correcting codes and qudit graph states. This method in fact constitutes a general recipe for obtaining multipartitite entangled states from classical codes. Furthermore, we show that at least for a large subset of this new class of k-UNI states, the states are inequivalent under stochastic local operations and classical communication. This subset is defined by an iterative procedure for constructing a hierarchy of k-UNI graph states.

I. INTRODUCTION

Multipartite entanglement is at the very heart of quantum information theory. In recent years, significant effort has been devoted to characterizing the entanglement properties of multipartite quantum states and constructing new examples of highly entangled states [1–8]. Much of this effort has focused on special classes of states such as graph states [9, 10], k-uniform (k-UNI) and absolutely maximally entangled (AME) states [6, 7, 11, 12], which are critical resources for measurement-based quantum computing [13], quantum networking [12, 14, 15], and quantum error correction [6, 10, 16–19].

Graph states are multipartite stabilizer states in which each vertex of a given graph represents a qudit, and the graph adjacency matrix defines the stabilizer generators [9, 10]. k-UNI states are highly entangled pure states that have the property that all of their k-qudit reduced density matrices are maximally mixed [19–23]. That is, the state $|\psi\rangle$ is a k-UNI state if

$$\rho_S = \mathrm{Tr}_{S^c} |\psi\rangle\langle\psi| \propto \mathbb{1} \qquad \forall S \subset \{1,\dots,n\}, |S| \leq k \ ,$$

where S^c denotes the complementary set of S. AME states correspond to the special case where $k = \lfloor n/2 \rfloor$, so that completely mixed states are obtained for any bipartition of the n qudits.

In light of the importance of graph and k-UNI states, it is interesting to consider what states lie at the intersection of these two classes. In addition to enabling interesting applications, k-UNI states that admit a graphical description can provide a powerful framework for investigating the entanglement structure of k-UNI states more generally. Moreover, the application of graph state techniques can facilitate finding new examples of k-UNI states, an endeavor that is generally not straightforward. So far, the only known systematic method of constructing k-UNI graph states is to start from a k-UNI state defined in terms of classical error correcting codes and to Fourier transform this into a graph state. This approach only yields a limited class of states corresponding to complete bipartite graphs [6, 11, 12]. Whether or not a broader class of k-UNI graph states exists and how to find it has remained unclear (in this regards also see [7]).

In this work, we uncover a large class of entangled states that are both graph states and k-UNI or AME states. We do this by finding a general set of constraints on the graph adjacency matrix that guarantee the resulting state is k-UNI. These constraints allow us to go well beyond the special case of complete bipartite graphs. We show that explicit examples of such states can be obtained by constructing the adjacency matrix from classical error correcting codes. We then focus on a particular subset of these states that can be generated by applying an iterative procedure to produce a hierarchy of k-UNI and AME graph states. We show that at each level of this iterative process, the resulting state remains k-UNI, but the states from different levels cannot be converted into each other using stochastic local operations and classical communication (SLOCC).

The paper is organized as follows. In Sec. II, we first review the method of constructing k-UNI and AME states from classical linear codes, then in Sec. III we present our general method of finding k-UNI graph states. In Sec. IV, we present the hierarchical graph state procedure. In Sec. V, we show that the generalized method of constructing k-UNI states from codes is the first level of this hierarchical procedure. Finally, in Sec. VI we show the states constructed at different levels of the hierarchy belong to different SLOCC classes.

II. CONSTRUCTING k-UNI STATES FROM CLASSICAL CODES

The connection between classical codes and k-UNI states has been shown to provide a systematic method of constructing a large set of k-UNI states [5–7]. In this