


2020–2022





arXiv:2112.14682v1 [quant-ph] 29 Dec 2021

Exact quantum query complexity of computing Hamming weight modulo powers of two and three

Arjan Cornelissen* Nikhil S. Mande† Maris Ozols‡ Ronald de Wolf§

Abstract

We study the problem of computing the Hamming weight of an n-bit string modulo m, for any positive integer $m \leq n$ whose only prime factors are 2 and 3. We show that the exact quantum query complexity of this problem is $\lceil n(1-1/m) \rceil$. The upper bound is via an iterative query algorithm whose core components are:

- the well-known 1-query quantum algorithm (essentially due to Deutsch) to compute the Hamming weight a 2-bit string mod 2 (i.e., the parity of the input bits), and
- a new 2-query quantum algorithm to compute the Hamming weight of a 3-bit string mod 3.

We show a matching lower bound (in fact for arbitrary moduli m) via a variant of the polynomial method [de Wolf, SIAM J. Comput., 32(3), 2003]. This bound is for the weaker task of deciding whether or not a given n-bit input has Hamming weight 0 modulo m, and it holds even in the stronger *non-deterministic* quantum query model where an algorithm must have positive acceptance probability iff its input evaluates to 1. For $m > 2$ our lower bound exceeds $n/2$, beating the best lower bound provable using the general polynomial method [Theorem 4.3, Beals et al., J. ACM 48(4), 2001].

1 Introduction

Query complexity considers the number of queries to input variables needed to compute some function of the input. *Quantum* query complexity has been well studied over the last few decades, and has been the source of many new quantum algorithms [DJ92, Sim97, Sho97, Gro96, Amb07, MNRS11]. An important special case is where the function we want to compute of input $x \in \{0,1\}^n$ only depends on the Hamming weight $|x|$, i.e., the number of 1s in x. Such functions are called *symmetric*, and well-studied examples of symmetric Boolean-valued functions include AND, OR, Majority, Parity, etc. The quantum query complexity (allowing small error probability) of all such functions was tightly characterized in [Wol08]. Another important class of symmetric problems is *approximate counting*, where we try to approximate the Hamming weight $|x|$ itself rather than

*Institute for Logic, Language, and Computation, University of Amsterdam and QuSoft. arjan@cwi.nl

†CWI, Amsterdam. Nikhil.Mande@cwi.nl
Supported by the Dutch Research Council (NWO) through QuantERA ERA-NET Cofund project QuantAlgo (project number 680-91-034).
‡Institute for Logic, Language, and Computation, Korteweg-de Vries Institute for Mathematics, and Institute for Theoretical Physics, University of Amsterdam and QuSoft.
Supported by an NWO Vidi grant (Project No. VI.Vidi.192.109).
marozols@gmail.com

§QuSoft, CWI and University of Amsterdam, the Netherlands.
Partially supported by the Dutch Research Council (NWO/OCW), as part of the Quantum Software Consortium programme (project number 024.003.037), and through QuantERA ERA-NET Cofund project QuantAlgo (680-91-034).
rdewolf@cwi.nl

