

2021–2026

Hardware-efficient entangled measurements for variational quantum algorithms

Francisco Escudero,[1,2] David Fernández-Fernández,[1,3] Gabriel Jaumà,[1] Guillermo F. Peñas,[1] and Luciano Pereira[1,*]

[1] *Instituto de Física Fundamental, IFF-CSIC, Calle Serrano 113b, 28006 Madrid, Spain*
[2] *CWI & QuSoft, Science Park 123, 1098 XG Amsterdam, The Netherlands*
[3] *Instituto de Ciencia de Materiales de Madrid, ICMM-CSIC, 28049 Madrid, Spain*

Variational algorithms have received significant attention in recent years due to their potential to solve practical problems using noisy intermediate-scale quantum (NISQ) devices. A fundamental step of these algorithms is the evaluation of the expected value of Hamiltonians, and hence efficient schemes to perform this task are required. The standard approach employs local measurements of Pauli operators and requires a large number of circuits. An alternative is to make use of entangled measurements, which might introduce additional gates between physically disconnected qubits that harm the performance. As a solution to this problem, we propose hardware-efficient entangled measurements (HEEM), that is, measurements that permit only entanglement between physically connected qubits. We show that this strategy enhances the evaluation of molecular Hamiltonians in NISQ devices by reducing the number of circuits required without increasing their depth. We provide quantitative metrics of how this approach offers better results than local measurements and arbitrarily entangled measurements. We estimate the ground-state energy of the H_2O molecule with classical simulators and quantum hardware using the variational quantum eigensolver with HEEM.

arXiv:2202.06979v4 [quant-ph] 26 May 2023

I. INTRODUCTION.

We are currently in the era of noisy intermediate-scale quantum computers (NISQ). The main limitations of these devices are short coherence times and noisy entanglement gates; therefore, NISQ circuits must inevitably have a low depth [1]. Given that, a lot of effort has been devoted to the design and implementation of quantum algorithms that only use low-depth circuits [2–5]. Among such algorithms, one family that has gained attention is variational quantum algorithms (VQAs) [6–8]: hybrid quantum-classical methods where a classical computer guides a quantum computer to produce variational quantum states and to measure their expected value, with the goal of minimizing an objective function encoded in a Hamiltonian. The most famous VQAs are the variational quantum eigensolver (VQE) [9] and the quantum approximate optimization algorithm (QAOA) [10]. Multiple VQAs have been applied in a wide range of areas, such as chemistry [11–14], finance [15, 16], traffic prediction [17], machine learning [18–21], entanglement detection [22–24], and differential equations [25–27].

Despite the great advances made in recent years, implementing VQA remains a challenge. One of the main drawbacks is the large number of measurements required to evaluate the objective function. Such evaluation can be done by decomposing the Hamiltonian on the basis of tensor products of Pauli operators, also called Pauli strings, and then measuring each of these terms independently. Using this approach, the number of measurements needed to evaluate the objective function is equal to the Pauli terms of the Hamiltonian, which scales as N^4 for typical instances such as second-quantized chemical Hamiltonians on N qubits [28, 29]. The preparation and measurement of each circuit require a non-negligible amount of time and resources; thus, decreasing the number of circuits is essential to speed up VQAs and to reach realistic applications of quantum computing.

Several methods have been proposed to reduce the total number of measurements required to efficiently measure observables, such as classical shadows [30, 31], quantum tomography [32–35], machine learning [36, 37], sampling methods [38, 39], hamiltonian moments [40], and adaptive protocols [41]. Other proposals are grouping methods, which exploit the commutative relation between the Pauli strings to make groups that can be measured simultaneously, reducing the total number of required experiments. The most widely known approach is the grouping with tensor product basis (TPB) [12–14, 42, 43], which uses qubit-wise commutativity and does not require entanglement. Another alternative is to use entangled measurements, which further reduces the number of measurements compared to TPB [44–47]. However, this last approach assumes unlimited entanglement resources and is not suitable for NISQ devices. There is a midpoint between the two extreme alternatives of assuming limitless entanglement or none at all: using measurements whose entanglement requirements are within the limits of NISQ devices. There are several works in this line [48–51], nevertheless, none of these techniques takes into account the connectivity of the particular quantum processor where the algorithm is run.

In this article, we address the problem of grouping Pauli strings with entangled measurements (EMs), but only between physically connected qubits, that is, hardware-efficient entangled measurements (HEEMs). Given a set of Pauli strings and the processor connectivity, there is a vast number of possible HEEMs, some of which will be more effective than others. Finding the optimal HEEM requires, among other things, finding the optimal mapping between the theoretical qubits of the algorithm and the physical qubits of the device.



* luciano.ivan@iff.csic.es