


# Memory Compression with Quantum Random-Access Gates


Harry Buhrman* harry.buhrman@cwi.nl

Bruno Loff† bruno.loff@gmail.com

Subhasree Patro* subhasree.patro@cwi.nl

Florian Speelman* f.speelman@uva.nl

*QuSoft, University of Amsterdam, CWI Amsterdam,
†University of Porto and INESC-Tec


March 14, 2022

arXiv:2203.05599v1 [quant-ph] 10 Mar 2022


**Abstract**

In the classical RAM, we have the following useful property. If we have an algorithm that uses $M$ memory cells throughout its execution, and in addition is sparse, in the sense that, at any point in time, only $m$ out of $M$ cells will be non-zero, then we may "compress" it into another algorithm which uses only $m \log M$ memory and runs in almost the same time. We may do so by simulating the memory using either a hash table, or a self-balancing tree.

We show an analogous result for quantum algorithms equipped with quantum random-access gates. If we have a quantum algorithm that runs in time $T$ and uses $M$ qubits, such that the state of the memory, at any time step, is supported on computational-basis vectors of Hamming weight at most $m$, then it can be simulated by another algorithm which uses only $O(m \log M)$ memory, and runs in time $\tilde{O}(T)$.

We show how this theorem can be used, in a black-box way, to simplify the presentation in several papers. Broadly speaking, when there exists a need for a space-efficient history-independent quantum data-structure, it is often possible to construct a space-inefficient, yet sparse, quantum data structure, and then appeal to our main theorem. This results in simpler and shorter arguments.


## Contents


**1 Introduction** **1**

**2 Definitions** **2**
2.1 Quantum Random-Access Machine (QRAM) . . . 3
2.2 Sparse QRAM algorithms . . . 3
2.3 Time complexity of simple operations (the constant $\gamma$) . . . 3
2.4 Controlled unitaries . . . 4

**3 Compressing sparse algorithms using quantum radix trees** **4**
3.1 Radix Tree . . . 5
3.2 Prefix-Sum Tree . . . 6
3.3 Quantum Radix Tree . . . 7
3.4 The simulation . . . 10

**4 Simplifications of previous work** **10**
4.1 Ambainis' Walk Algorithm for Element Distinctness . . . 11
4.2 Quantum Algorithms for Closest-Pair and related Problems . . . 12
4.3 Fine-Grained Complexity via Quantum Walks . . . 15

**5 Acknowledgments** **15**


