

Generating k EPR-pairs from an n-party resource state

Sergey Bravyi[1], Yash Sharma[2], Mario Szegedy[2], and Ronald de Wolf[3]

[1]IBM Quantum, IBM T.J. Watson Research Center, Yorktown Heights, NY 10598, USA.
[2]Rutgers University
[3]QuSoft, CWI and University of Amsterdam, the Netherlands.

arXiv:2211.06497v5 [quant-ph] 9 May 2024

Motivated by quantum network applications over classical channels, we initiate the study of n-party resource states from which LOCC protocols can create EPR-pairs between any k disjoint pairs of parties. We give constructions of such states where k is not too far from the optimal $n/2$ while the individual parties need to hold only a constant number of qubits. In the special case when each party holds only one qubit, we describe a family of n-qubit states with k proportional to $\log n$ based on Reed-Muller codes, as well as small numerically found examples for $k = 2$ and $k = 3$. We also prove some lower bounds, for example showing that if $k = n/2$ then the parties must have at least $\Omega(\log \log n)$ qubits each.

1 Introduction

1.1 Generating EPR-pairs from a resource state

Quantum communication networks combine several quantum computers to enable them to solve interesting tasks from cryptography, communication complexity, distributed computing etc. Building a large-scale quantum communication network is a daunting task that will take many years, but networks with a few small quantum computers are under construction and may start to appear in the next few years [36].




Figure 1: State of $n = 4$ parties with 6 EPR-pairs

These networks are either based on channels that physically communicate quantum states, or rely on classical communication in tandem with shared entanglement, or a combination of both. Communication over classical channels cannot increase entanglement, so in the absence of quantum channels we have to rely on prior entangled states. For example, if two parties share an EPR-pair, $\frac{1}{\sqrt{2}}(|00\rangle + |11\rangle)$, then one party can transmit ("teleport") a qubit to the other via two classical bits of communication, consuming the EPR-pair in the process [4]. If we want to enable many qubits to be sent in this way, then we could start with an entangled state where each pair among the n parties shares its own EPR-pair. This would allow any pair to exchange a qubit, but would require us to start with a rather large initial entangled state of $\binom{n}{2}$ EPR-pairs, and each of the n parties would need to hold $n-1$ qubits (see Figure 1 for $n = 4$).

Sergey Bravyi: sbravyi@us.ibm.com
Yash Sharma: yash.sharma@rutgers.edu
Mario Szegedy: szegedy@cs.rutgers.edu
Ronald de Wolf: rdewolf@cwi.nl, Partially supported by the Dutch Research Council (NWO) through Gravitation-grant Quantum Software Consortium, 024.003.037.