





arXiv:2211.09686v1 [quant-ph] 17 Nov 2022

An efficient combination of quantum error correction and authentication

Yfke Dulek[1], Garazi Muguruza[2], and Florian Speelman[2]

[1] *QuSoft, CWI Amsterdam, Science Park 123, 1098 XG Amsterdam, The Netherlands*
[2] *QuSoft, University of Amsterdam, Science Park 904, 1098 XH Amsterdam, The Netherlands*

November 18, 2022

Abstract

When sending quantum information over a channel, we want to ensure that the message remains intact. Quantum error correction and quantum authentication both aim to protect (quantum) information, but approach this task from two very different directions: error-correcting codes protect against probabilistic channel noise and are meant to be very robust against small errors, while authentication codes prevent adversarial attacks and are designed to be very sensitive against any error, including small ones.

In practice, when sending an authenticated state over a noisy channel, one would have to wrap it in an error-correcting code to counterbalance the sensitivity of the underlying authentication scheme. We study the question of whether this can be done more efficiently by combining the two functionalities in a single code. To illustrate the potential of such a combination, we design the threshold code, a modification of the trap authentication code [BGS13] which preserves that code's authentication properties, but which is naturally robust against depolarizing channel noise. We show that the threshold code needs polylogarithmically fewer qubits to achieve the same level of security and robustness, compared to the naive composition of the trap code with any concatenated CSS code. We believe our analysis opens the door to combining more general error-correction and authentication codes, which could improve the practicality of the resulting scheme.

Keywords: quantum cryptography, quantum authentication, quantum error-correction, trap code.