


Quantum majority vote

Harry Buhrman* Noah Linden† Laura Mančinska‡ Ashley Montanaro§
Maris Ozols¶

November 22, 2022

arXiv:2211.11729v1 [quant-ph] 21 Nov 2022

Abstract

Majority vote is a basic method for amplifying correct outcomes that is widely used in computer science and beyond. While it can amplify the correctness of a quantum device with classical output, the analogous procedure for quantum output is not known. We introduce *quantum majority vote* as the following task: given a product state $|\psi_1\rangle \otimes \cdots \otimes |\psi_n\rangle$ where each qubit is in one of two orthogonal states $|\psi\rangle$ or $|\psi^\perp\rangle$, output the majority state. We show that an optimal algorithm for this problem achieves worst-case fidelity of $1/2 + \Theta(1/\sqrt{n})$. Under the promise that at least $2/3$ of the input qubits are in the majority state, the fidelity increases to $1 - \Theta(1/n)$ and approaches 1 as n increases.

We also consider the more general problem of computing any symmetric and equivariant Boolean function $f : \{0,1\}^n \to \{0,1\}$ in an unknown quantum basis, and show that a generalization of our quantum majority vote algorithm is optimal for this task. The optimal parameters for the generalized algorithm and its worst-case fidelity can be determined by a simple linear program of size $O(n)$. The time complexity of the algorithm is $O(n^4 \log n)$ where n is the number of input qubits.

Contents

1 Introduction **3**
1.1 Problem . . . 3
1.2 Our results . . . 5
1.3 Related work . . . 6
1.4 Open problems . . . 7
1.5 Outline . . . 8

2 Preliminaries **9**
2.1 Mathematical preliminaries . . . 9
2.2 Computing functions in a basis-independent way . . . 11
2.3 Symmetric and equivariant Boolean functions . . . 12
2.4 Impossibility of perfect quantum majority . . . 13
2.5 Symmetries of optimal algorithms . . . 14

*QuSoft, CWI, and University of Amsterdam, harry.buhrman@cwi.nl.
†University of Bristol, n.linden@bristol.ac.uk.
‡University of Copenhagen, mancinska@math.ku.dk.
§Phasecraft Ltd and University of Bristol, ashley.montanaro@bristol.ac.uk.
¶QuSoft and University of Amsterdam, marozols@gmail.com.

