

2021–2025



Single-qubit loss-tolerant quantum position verification protocol secure against entangled attackers

Llorenç Escolà-Farràs[1,2] and Florian Speelman[1,2]

[1] *QuSoft, CWI Amsterdam, Science Park 123, 1098 XG Amsterdam, The Netherlands*
[2] *Multiscale Networked Systems (MNS), Informatics Institute, University of Amsterdam, Science Park 904, 1098 XH Amsterdam, The Netherlands*

July 10, 2025

arXiv:2212.03674v3 [quant-ph] 9 Jul 2025

Abstract

Protocols for quantum position verification (QPV) which combine classical and quantum information are insecure in the presence of loss. We study the exact loss-tolerance of the most popular protocol for QPV, which is based on BB84 states, and generalizations of this protocol. By bounding the winning probabilities of a variant of the monogamy-of-entanglement game using semidefinite programming (SDP), we find tight bounds for the relation between loss and error for these extended non-local games.

These new bounds enable the usage of QPV protocols using more-realistic experimental parameters. We show how these results transfer to the variant protocol which combines n bits of classical information with a single qubit, thereby exhibiting a protocol secure against a linear amount of entanglement (in the classical information n) even in the presence of a moderate amount of photon loss. Moreover, this protocol stays secure even if the photon encoding the qubit travels arbitrarily slow in an optical fiber. We also extend this analysis to the case of more than two bases, showing even stronger loss-tolerance for that case.

Finally, since our semi-definite program bounds a monogamy-of-entanglement game, we describe how they can also be applied to improve the analysis of one-sided device-independent QKD protocols.

1 Introduction

Position-based cryptography (PBC), initially introduced by Chandran, Goyal, Moriarty and Ostrovsky [CGMO09], aims to allow a party to use its geographical location as a credential to implement various cryptographic protocols. An important building block for PBC is so-called Position Verification (PV), where an untrusted prover P wants to convince a set of verifiers $V_0, \ldots, V_k$ that she is at a certain position r. In [CGMO09] it was proven that no secure classical protocol for position verification can exist, since there exists a general attack based on copying classical information. Adrian Kent first studied PV protocols that use quantum information in 2002, originally named *quantum tagging* [KMSB06, KMS11] and currently called Quantum Position Verification (QPV) in the literature. Due to the no-cloning theorem [WZ82], attacks based on simply copying information do not transfer to the quantum setting. Nevertheless, unconditionally secure QPV was proven to be impossible, with [BCF+14] showing that any QPV could be attacked with double-exponential entanglement, which was later improved to exponential entanglement [BK11].

On the other side, it is possible to prove a linear lower bound for the amount of entanglement [BK11, TFKW13]—an exponential gap. Still, the extreme inefficiency of the general attack left the possibility open that QPV could be shown secure if we consider attackers that are bounded in some (realistic) way. Ideally that would mean a protocol which requires an exponential amount of entanglement to attack, but any provable gap between the hardness of executing the protocol versus breaking the protocol could be interesting. This possibility created the opportunity for many interesting follow-up work, showing security under model assumptions such as finding clever

