

2022–2024

Maximum tolerable excess noise in CV-QKD and improved lower bound on two-way capacities

Francesco Anna Mele,[1,*] Ludovico Lami,[2,3,4,5,†] and Vittorio Giovannetti[1,‡]

[1] *NEST, Scuola Normale Superiore and Istituto Nanoscienze, Consiglio Nazionale delle Ricerche, Piazza dei Cavalieri 7, IT-56126 Pisa, Italy*
[2] *QuSoft, Science Park 123, 1098 XG Amsterdam, the Netherlands*
[3] *Korteweg-de Vries Institute for Mathematics, University of Amsterdam, Science Park 105-107, 1098 XG Amsterdam, the Netherlands*
[4] *Institute for Theoretical Physics, University of Amsterdam, Science Park 904, 1098 XH Amsterdam, the Netherlands*
[5] *Institut für Theoretische Physik und IQST, Universität Ulm, Albert-Einstein-Allee 11, D-89069 Ulm, Germany*

arXiv:2303.12867v4 [quant-ph] 24 Jan 2025

The two-way capacities of quantum channels determine the ultimate entanglement and secret-key distribution rates achievable by two distant parties that are connected by a noisy transmission line, in absence of quantum repeaters. Since repeaters will likely be expensive to build and maintain, a central open problem of quantum communication is to understand what performances are achievable without them. In this paper, we find a new lower bound on the energy-constrained and unconstrained two-way quantum and secret-key capacities of all phase-insensitive bosonic Gaussian channels, namely thermal attenuator, thermal amplifier, and additive Gaussian noise, which are realistic models for the noise affecting optical fibres or free-space links. Ours is the first nonzero lower bound on the two-way quantum capacity in the parameter range where the (reverse) coherent information becomes negative, and it shows explicitly that entanglement distribution is always possible when the channel is not entanglement breaking. This completely solves a crucial open problem of the field, namely, establishing the maximum excess noise which is tolerable in continuous-variable quantum key distribution. In addition, our construction is fully explicit, i.e. we devise and optimise a concrete entanglement distribution and distillation protocol that works by combining recurrence and hashing protocols.

Quantum key distribution (QKD) stands as the gold standard for unconditionally secure communication. Since its inception in 1984 [1], QKD has transitioned from a theoretical concept to a commercially viable technology. Continuous-variable systems [2], such as electromagnetic modes, offer a powerful approach to QKD, known as CV-QKD [3–5]. Unlike its discrete-variable counterpart [4], CV-QKD is expected to be seamlessly integrated into existing optical fibre-based Internet infrastructure in the near future [4, 6–10], making it highly practical for real-world applications. A significant challenge in this field, essential for the development of a large-scale quantum internet [4, 11], is extending CV-QKD over long distances without intermediate nodes [4]. In recent years, numerous experiments have been setting new distance records, achieving CV-QKD across optical fibres exceeding one hundred kilometers in length [6–10]. This progress prompts a critical question: "What is the maximum achievable distance of CV-QKD according to the laws of quantum physics?" Equivalently, "What is the maximum tolerable excess noise in CV-QKD?" This has been identified as a crucial open problem in the field [12, Section 7].

In quantum Shannon theory [13, 14], the capacities of quantum channels determine the ultimate limits of quantum communication which are achievable across the channel. Specifically, the *secret-key capacity* $K(\Phi)$ and the *two-way quantum capacity* $Q_2(\Phi)$ of a quantum channel Φ, collectively called the *two-way capacities*, are the maximum rates of secret-key bits and entanglement bits (or *ebits*), respectively, achievable across Φ when the sender (Alice) and the receiver (Bob) are assisted by two-way classical communication [13, 14]. These capacities quantify the optimal performance for QKD and entanglement distribution. Importantly, QKD across Φ is achievable if and only if $K(\Phi) > 0$, while entanglement distribution across Φ is achievable if and only if $Q_2(\Phi) > 0$. Since in practice only a finite amount of energy can be utilised in a communication protocol, it is common to consider the *energy-constrained* two-way capacities [15]. These are denoted as $K(\Phi, N_s)$ and $Q_2(\Phi, N_s)$, where N_s represents the maximum average photon number per input signal to the channel Φ. Since an ebit can be converted into a secret-key bit [16], these capacities satisfy $K(\Phi, N_s) \geq Q_2(\Phi, N_s)$.

Within the framework of quantum optical communication, a realistic model to describe optical fibres is the *thermal attenuator* $\mathscr{E}_{\lambda,\nu}$ [2, 12, 17]. It is a single-mode quantum channel characterised by two parameters: the transmissivity $\lambda \in [0, 1]$ of the fibre and the added thermal noise $\nu \in [0, \infty)$ [2]. We provide a detailed definition

* francesco.mele@sns.it
† ludovico.lami@gmail.com
‡ vittorio.giovannetti@sns.it