

2022–2024

The Foliage Partition: An Easy-to-Compute LC-Invariant for Graph States

Adam Burchardt[1] and Frederik Hahn[2,3]

[1]QuSoft, CWI and University of Amsterdam, Science Park 123, 1098 XG Amsterdam, the Netherlands
[2]Electrical Engineering and Computer Science Department, Technische Universität Berlin, 10587 Berlin, Germany
[3]Dahlem Center for Complex Quantum Systems, Freie Universität Berlin, 14195 Berlin, Germany

arXiv:2305.07645v2 [quant-ph] 14 Apr 2025

This paper introduces the foliage partition, an easy-to-compute LC-invariant for graph states, of computational complexity $\mathcal{O}(n^3)$ in the number of qubits. Inspired by the foliage of a graph, our invariant has a natural graphical representation in terms of leaves, axils, and twins. It captures both, the connection structure of a graph and the 2-body marginal properties of the associated graph state. We relate the foliage partition to the size of LC-orbits and use it to bound the number of LC-automorphisms of graphs. We also show the invariance of the foliage partition when generalized to weighted graphs and qudit graph states.

1 Introduction

Graph states play an essential role in quantum information theory and quantum computing [1, 2, 3, 4]. As examples of stabilizer states, graph states can be directly implemented on quantum computers [5, 6, 7]. As their name suggests, graph states can be visually represented by graphs, with vertices corresponding to qubits and edges representing controlled two-qubit operations for the experimental implementation of the graph state. In the language of graph theory, local Clifford (LC) operations acting on a graph state correspond to local complementations of the associated graph.

Three main questions surrounding graph states include their entanglement properties [8, 9, 10], their equivalence under local operations [11, 12, 13, 14, 15, 16, 17], and their classification [14, 18, 19]. Considerable effort has been made to address these questions: first, an efficient algorithm to determine the LC-equivalence of given graph states with complexity $\mathcal{O}(n^4)$ in the number of qubits n has been discovered [11, 12, 20]; second, a finite set of invariants which completely characterizes the LC-equivalence class of any graph state –and more generally, any stabilizer state– has been identified [21, 22]; third, graph states have been classified up to 12 qubits [18] and there are lower and upper bounds on the number of non-equivalent graph states for a given number of qubits [14]. Our focus is on the second problem as we introduce an easy-to-compute LC-invariant for graph states.

Although known invariants completely characterize the LC-equivalence class of any graph state, they are computationally inefficient [21, 22], requiring knowledge of the given

Adam Burchardt: adam.burchardt.uam@gmail.com,
Frederik Hahn: mail@frederikhahn.eu,

Both authors contributed equally to this work.

