







Relating non-local quantum computation to information theoretic cryptography

Rene Allerstorfer[2], Harry Buhrman[2,3], Alex May[1], Florian Speelman[2,3], and Philip Verduyn Lunel[2]

[1]Perimeter Institute for Theoretical Physics
[2]QuSoft, CWI Amsterdam
[3]University of Amsterdam

arXiv:2306.16462v6 [quant-ph] 24 Jun 2024

Non-local quantum computation (NLQC) is a cheating strategy for position-verification schemes, and has appeared in the context of the AdS/CFT correspondence. Here, we connect NLQC to the wider context of information theoretic cryptography by relating it to a number of other cryptographic primitives. We show one special case of NLQC, known as f-routing, is equivalent to the quantum analogue of the conditional disclosure of secrets (CDS) primitive, where by equivalent we mean that a protocol for one task gives a protocol for the other with only small overhead in resource costs. We further consider another special case of position-verification, which we call coherent function evaluation (CFE), and show CFE protocols induce similarly efficient protocols for the private simultaneous message passing (PSM) scenario. By relating position-verification to these cryptographic primitives, a number of results in the information theoretic cryptography literature give new implications for NLQC, and vice versa. These include the first sub-exponential upper bounds on the worst case cost of f-routing of $2^{O(\sqrt{n \log n})}$ entanglement, the first example of an efficient f-routing strategy for a problem believed to be outside $P/poly$, linear lower bounds on quantum resources for CDS in the quantum setting, linear lower bounds on communication cost of CFE, and efficient protocols for CDS in the quantum setting for functions that can be computed with quantum circuits of low T depth.

Rene Allerstorfer: Rene.Allerstorfer@cwi.nl
Harry Buhrman: Harry.Buhrman@cwi.nl
Alex May: amay@perimeterinstitute.ca
Florian Speelman: f.speelman@uva.nl
Philip Verduyn Lunel: philip.verduyn.lunel@cwi.nl

