

2022–2024

Optical fibres with memory effects and their quantum communication capacities

Francesco Anna Mele *NEST, Scuola Normale Superiore and Istituto Nanoscienze, Consiglio Nazionale delle Ricerche, Piazza dei Cavalieri 7, IT-56126 Pisa, Italy*
francesco.mele@sns.it
Giacomo De Palma *Department of Mathematics, University of Bologna, Piazza di Porta San Donato 5, 40126 Bologna BO, Italy*
giacomo.depalma@unibo.it
Marco Fanizza *Física Teòrica: Informació i Fenòmens Quàntics, Departament de Física, Universitat Autònoma de Barcelona, ES-08193 Bellaterra (Barcelona), Spain*
marco.fanizza@uab.cat
Vittorio Giovannetti *NEST, Scuola Normale Superiore and Istituto Nanoscienze, Consiglio Nazionale delle Ricerche, Piazza dei Cavalieri 7, IT-56126 Pisa, Italy*
vittorio.giovannetti@sns.it
Ludovico Lami *QuSoft, Science Park 123, 1098 XG Amsterdam, the Netherlands*
Korteweg-de Vries Institute for Mathematics, University of Amsterdam, Science Park 105-107, 1098 XG Amsterdam, the Netherlands
Institute for Theoretical Physics, University of Amsterdam, Science Park 904, 1098 XH Amsterdam, the Netherlands
ludovico.lami@gmail.com

arXiv:2309.17066v2 [quant-ph] 27 Jan 2025

***Abstract*—If the transmissivity of an optical fibre falls below a critical value, its use as a reliable quantum channel is known to be drastically compromised. However, if the memoryless assumption does not hold — e.g. when input signals are separated by a sufficiently short time interval — the validity of this limitation is put into question. In this work we introduce a model of optical fibre that can describe memory effects for long transmission lines. We then solve its quantum capacity, two-way quantum capacity, and secret-key capacity exactly. By doing so, we show that — due to the memory cross-talk between the transmitted signals — reliable quantum communication is attainable even for highly noisy regimes where it was previously considered impossible.**

***Index Terms*—Quantum Shannon Theory, Continuous Variable systems, Non-markovian noise, Memory effects in quantum communication, Long-distance quantum communication**

I. Introduction

The potential applications of a global quantum internet [1], [2] include secure communication [3], efficient entanglement and qubits distribution, enhanced quantum sensing capabilities [4], distributed and blind quantum computing [5], [6], as well as groundbreaking experiments in fundamental physics [4]. These applications heavily rely on establishing long-distance quantum communication across optical fibres or free-space links. However, the vulnerability of optical signals to noise poses a significant obstacle to achieving this goal. To overcome this challenge, one possible solution is to exploit quantum repeaters [7], [8] along the communication line. However, current implementations of quantum repeaters remain in the realm of proof-of-principle experiments. In addition, quantum repeaters will likely impose substantial demands on technology resources, making them potentially expensive. Consequently, a pressing problem is to develop protocols that can operate without — or with a modest number of — quantum repeaters. Recently, in [9], [10] a theoretical proof-of-principle solution to this problem that takes advantage of *memory effects* [11], [12] in optical fibres has been proposed.

Memory effects arise when signals are fed into the optical fibre separated by a sufficiently short time interval [11], [12], [13], [14]. In this scenario, the noise within the fibre is influenced by prior input signals, exhibiting a form of "memory." Consequently, the commonly assumed memoryless (iid) paradigm, which posits that noise acts uniformly and independently on each signal, becomes invalid. The exploration of memory effects in optical fibres has been extensively addressed in [15], [16], [17], [10], [9]. While these studies capture fundamental aspects of the problem, especially in the context of "short" communication lines, a more comprehensive analysis reveals limitations when extending these findings to practical configurations. Specifically, in scenarios involving "long" communication lines where consecutive signals continually interact throughout the entire length of the fibre, the existing models become inadequate, as

