



2022–2024



arXiv:2312.03188v2 [quant-ph] 21 May 2024

EFFICIENT QUANTUM CIRCUITS FOR PORT-BASED TELEPORTATION

DMITRY GRINKO[1], ADAM BURCHARDT[1], AND MARIS OZOLS[1,2]

Abstract. Port-based teleportation (PBT) is a variant of quantum teleportation that, unlike the canonical protocol by Bennett et al., does not require a correction operation on the teleported state. Since its introduction by Ishizaka and Hiroshima in 2008, no efficient implementation of PBT was known. We close this long-standing gap by building on our recent results on representations of partially transposed permutation matrix algebras and mixed quantum Schur transform. We construct efficient quantum algorithms for probabilistic and deterministic PBT protocols on n ports of arbitrary local dimension, both for EPR and optimized resource states. We describe two constructions based on different encodings of the Gelfand–Tsetlin basis for n qudits: a standard encoding that achieves $\tilde{O}(n)$ time and $O(n\log(n))$ space complexity, and a Yamanouchi encoding that achieves $\tilde{O}(n^2)$ time and $O(\log(n))$ space complexity, both for constant local dimension and target error. We also describe efficient circuits for preparing the optimal resource states.

Contents

1. Introduction 2
1.1. Background 2
1.2. Types of PBT protocols 2
1.3. Summary of our results 3
1.4. Related work 3
2. Preliminaries 3
2.1. Notation 3
2.2. Representation theory of the partially transposed permutation algebra 4
2.3. Mixed quantum Schur transform 5
2.4. PBT measurement and figures of merit 7
2.5. The standard PGM 7
2.6. POVMs for deterministic and probabilistic PBT 8
2.7. Naimark dilations and implementation of measurements 9
3. Efficient quantum algorithms for PBT in standard encoding 11
3.1. Naimark's dilation of the standard PGM 11
3.2. Quantum circuit for standard PGM 13
3.3. Quantum circuit for deterministic PBT measurement 17
3.4. Quantum circuit for probabilistic PBT measurement with EPR resource state 17
3.5. Efficient quantum algorithms for generic PBT measurements 18
3.6. Exponentially improved lower bound for non-local quantum computation 19
4. Logarithmic space PBT via Yamanouchi encoding 20
5. Quantum circuits for optimized resource states 22
Acknowledgements 25
References 25



[1]Institute for Logic, Language, and Computation, University of Amsterdam and QuSoft, Amsterdam, The Netherlands
[2]Korteweg-de Vries Institute for Mathematics and Institute for Theoretical Physics, University of Amsterdam, The Netherlands
E-mail addresses: dmitry.grinko@cwi.nl, adam.burchardt@cwi.nl, marozols@gmail.com.