

2021–2025

Lower Bounds for Unitary Property Testing with Proofs and Advice

Jordi Weggemans

QuSoft & CWI, Amsterdam, the Netherlands

arXiv:2401.07912v3 [quant-ph] 17 Apr 2025

In unitary property testing a quantum algorithm, also known as a *tester*, is given query access to a black-box unitary and has to decide whether it satisfies some property. We propose a new technique for proving lower bounds on the quantum query complexity of unitary property testing and related problems, which utilises its connection to unitary channel discrimination. The main advantage of this technique is that all obtained lower bounds hold for any C-tester with $\mathsf{C} \subseteq \mathsf{QMA}(2)/\mathsf{qpoly}$, showing that even having access to *both* (unentangled) quantum proofs and quantum advice does not help for many unitary property testing problems.

We apply our technique to prove lower bounds for problems like quantum phase estimation, the entanglement entropy problem, quantum Gibbs sampling and more, removing all logarithmic factors in the lower bounds obtained by the sample-to-query lifting theorem of Wang and Zhang (2023). As a direct corollary, we show that there exist quantum oracles relative to which $\mathsf{QMA}(2) \not\subset \mathsf{SBQP}$ and $\mathsf{QMA}/\mathsf{qpoly} \not\subset \mathsf{SBQP}$. The former shows that, at least in a black-box way, having unentangled quantum proofs does not help in solving problems that require high precision.

1 Introduction

Quantum query complexity is the study of how many queries a quantum algorithm has to make to some black-box input X to decide whether X satisfies some property $\mathcal{P}$. Whilst quantum query complexity conventionally focuses on X being inherently classical (i.e., a classical bit string), it is also possible to consider the setting where X is some black-box unitary. Whilst the former (which we call classical property testing) is very useful in obtaining insights into the differences in computational power between different classes of computation, classical or quantum, the latter (called unitary property testing) gives another way to compare inherently quantum classes. These problems, first studied by Wang [1], got considerably more attention recently [2, 3, 4].

Query complexities can vastly differ among different classes of computational models. For example, the search problem, which is to decide whether a string of length N is either the all-zeros string or has at least one entry with a '1', is known to have classical query complexity of $\Theta(N)$ and quantum query complexity of $\Theta(\sqrt{N})$ [5, 6]. However, given a string by an untrusted prover, the query complexity of the search problem is just 1 in both cases. A similar result holds for a unitary property testing analogue of search as introduced by Aaronson and Kuperberg [7], where one has to decide whether a given black-box unitary

Jordi Weggemans: jrw@cwi.nl, https://jordiweggemans.github.io

