

2021–2025

Finding quantum partial assignments by search-to-decision reductions

Jordi Weggemans*

QuSoft & CWI, Amsterdam, the Netherlands

February 5, 2025

arXiv:2408.03986v2 [quant-ph] 4 Feb 2025

Abstract

In computer science, many search problems are reducible to decision problems, which implies that finding a solution is as hard as deciding whether a solution exists. A quantum analogue of search-to-decision reductions would be to ask whether a quantum algorithm with access to a QMA oracle can construct QMA witnesses as quantum states. By a result from Irani, Natarajan, Nirkhe, Rao, and Yuen (CCC '22), it is known that this does not hold relative to a quantum oracle, unlike the cases of NP, MA, and QCMA where search-to-decision relativizes.

We prove that if one is not interested in the quantum witness as a quantum state but only in terms of its partial assignments, i.e. the *reduced density matrices*, then there exists a classical polynomial-time algorithm with access to a QMA oracle that outputs approximations of the density matrices of a near-optimal quantum witness, for any desired constant locality and inverse polynomial error. Our construction is based on a circuit-to-Hamiltonian mapping that approximately preserves near-optimal QMA witnesses and a new QMA-complete problem, *Low-energy Density Matrix Verification*, which is called by the QMA oracle to adaptively construct approximately consistent density matrices of a low-energy state.

1 Introduction

Decision (or promise) problems are arguably the central objects of study in computational complexity theory. While resolving a decision problem provides information about the *existence* of a solution, it does not provide the solution itself. Fortunately, *search problems*, where the task is to output an actual solution, are often reducible to their related decision problems. In this context, one generally considers *Turing reductions*: here, one has access to an oracle capable of solving a class of decision problems, which is then used as a subroutine to solve the desired search problem.

As an example, consider a formula ϕ corresponding to a Boolean satisfiability (SAT) problem on n bits, and assume that we have access to an NP oracle. Under the assumption that ϕ is satisfiable, one can find a solution x^* such that $\phi(x^*) = 1$ in the following way: one queries the NP oracle adaptively to ask whether ϕ is satisfiable under the extra constraint that a certain subset of variables takes on specific values, i.e., under a fixed partial assignment. Every query to the oracle yields one bit of information about some x^*, and thus, after n queries, the algorithm has found a solution.[1] This strategy generally works for any problem in NP and can also be used to calculate the optimal value of an optimization problem up to exponential accuracy using binary search [Kre86].



*Email: jrw@cwi.nl.

[1] It can return any satisfying assignment if the solution is not unique.