

Bosonic randomized benchmarking with passive transformations

Mirko Arienzo,[1,*] Dmitry Grinko,[2,3] Martin Kliesch,[1] and Markus Heinrich[4,5]

[1] *Hamburg University of Technology, Institute for Quantum Inspired and Quantum Optimization, Blohmstraße 15, Hamburg, Germany*
[2] *Institute for Logic, Language and Computation, University of Amsterdam, Amsterdam, The Netherlands*
[3] *QuSoft, Amsterdam, The Netherlands*
[4] *Heinrich Heine University Düsseldorf, Faculty of Mathematics and Natural Sciences, Düsseldorf, Germany*
[5] *Institute for Theoretical Physics, University of Cologne, Cologne, Germany.*

Randomized benchmarking (RB) is the most commonly employed protocol for the characterization of unitary operations in quantum circuits due to its reasonable experimental requirements and robustness against state preparation and measurement (SPAM) errors. So far, the protocol has been limited to discrete or fermionic systems, whereas extensions to bosonic systems have been unclear for a long time due to challenges arising from the underlying bosonic Hilbert space. In this work, we close the gap for bosonic systems and develop an RB protocol to benchmark passive Gaussian transformations on any particle number subspace, which we call *passive bosonic RB*. The protocol is built on top of the recently developed filtered RB framework [1, 2] and is designed to isolate the multitude of exponential decays arising for passive bosonic transformations. We give explicit formulas and a Julia implementation for the necessary post-processing of the experimental data. We also analyze the sampling complexity of passive bosonic RB by deriving analytical expressions for the variance. They show a mild scaling with the number of modes, suggesting that passive bosonic RB is experimentally feasible for a moderate number of modes. We focus on experimental settings involving Fock states and particle number resolving measurements, but also discuss Gaussian settings, deriving first results for heterodyne measurements.

arXiv:2408.11111v2 [quant-ph] 14 May 2025

I. INTRODUCTION

The characterization of quantum devices, and, in particular, of the involved unitary operations, is a fundamental task in quantum information processing [3, 4]. While being a well-studied field for discrete variable systems, a similar standing for continuous variable (CV) systems has not yet been achieved. In fact, there are only very few works apart from CV tomography and the first rigorous guarantees for the latter were proven only recently [5, 6]. The required number of measurements is experimentally extremely challenging [7–13] and as a result, full quantum tomography is often not feasible for CV systems. Moreover, tomographic protocols typically suffer from state preparation and measurement (SPAM) errors, as in the discrete variable case.

Bosonic quantum systems play a major role in the design of quantum computing platforms. Most prominently, this includes photonic quantum computing as a popular proposal for scalable quantum computers [14–19]. The biggest advantages of this model rely on the implementation of particle sources, detectors, and linear optical circuits on the same integrated chips [20–23], and access to mixed schemes for quantum error correction [24]. Bosonic systems also offer interesting non-universal models of computation to test quantum supremacy, such as (Gaussian) boson sampling [25–27], which have been implemented successfully in real experiments recently [28–30].

Most challenges in the characterization of bosonic systems can be attributed to the particularities of the bosonic Hilbert space [7, 31]. For instance, protocols that rely on scrambling techniques via unitary designs are challenging to adapt, since Gaussian unitaries only form a unitary 1-design [32, 33], and unitary 2-designs cannot exist for CV systems, unless rigged Hilbert spaces are considered [34]. Such issues constrain characterization protocols to very specific settings, where the implemented unitary operators (which may include non-Gaussian single-mode unitaries) are only benchmarked w.r.t. a restricted set of input states [35].

For discrete variable systems, randomized benchmarking (RB) [36–45] is the most widespread family of protocols for the estimation of average gate fidelities. Its popularity is due to its robustness against SPAM errors and its rather low demands on the measurement effort [46]. The standard RB protocol is as follows: To a fixed initial state, apply a sequence of Haar-random (Clifford) unitaries, followed by a final *inversion gate* cancelling the action of the entire sequence. Then, the success probability of restoring the initial state decays exponentially with the length of the sequence, and the decay rate is a proxy for the average gate fidelity of the gate set.

Recent efforts led to general guarantees for RB protocols with general finite or compact groups [1, 2, 47–50] instead of only unitary 2-designs. Due to the non-existence of the latter, this generality is clearly important when considering RB of CV systems. However, there is still a fundamental problem: The RB signal generally consists of a linear combination of exponential decays in correspondence with the relevant irreducible representations (irreps) of the used group [1, 47, 48]. Estimating these decay r
is already difficult in practice if more than a few irr
are involved [1, 2] and may become impossible in the

* mirko.arienzo@tuhh.de