

2018–2022



2020–2022

arXiv:2408.12595v1 [quant-ph] 22 Aug 2024

Quantum Sabotage Complexity

Arjan Cornelissen* Nikhil S. Mande† Subhasree Patro‡

August 23, 2024

Abstract

Given a Boolean function $f : \{0,1\}^n \to \{0,1\}$, the goal in the usual query model is to compute f on an unknown input $x \in \{0,1\}^n$ while minimizing the number of queries to x. One can also consider a "distinguishing" problem denoted by f_{sab}: given an input $x \in f^{-1}(0)$ and an input $y \in f^{-1}(1)$, either all differing locations are replaced by a $*$, or all differing locations are replaced by †, and an algorithm's goal is to identify which of these is the case while minimizing the number of queries.

Ben-David and Kothari [ToC'18] introduced the notion of randomized sabotage complexity of a Boolean function to be the zero-error randomized query complexity of f_{sab}. A natural follow-up question is to understand $\mathsf{Q}(f_{\mathsf{sab}})$, the quantum query complexity of f_{sab}. In this paper, we initiate a systematic study of this. The following are our main results for all Boolean functions $f : \{0,1\}^n \to \{0,1\}$.

- If we have additional query access to x and y, then $\mathsf{Q}(f_{\mathsf{sab}}) = O(\min\{\mathsf{Q}(f), \sqrt{n}\})$.
- If an algorithm is also required to output a differing index of a 0-input and a 1-input, then $\mathsf{Q}(f_{\mathsf{sab}}) = O(\min\{\mathsf{Q}(f)^{1.5}, \sqrt{n}\})$.
- $\mathsf{Q}(f_{\mathsf{sab}}) = \Omega(\sqrt{\mathsf{fbs}(f)})$, where $\mathsf{fbs}(f)$ denotes the fractional block sensitivity of f. By known results, along with the results in the previous bullets, this implies that $\mathsf{Q}(f_{\mathsf{sab}})$ is polynomially related to $\mathsf{Q}(f)$.
- The bound above is easily seen to be tight for standard functions such as And, Or, Majority and Parity. We show that when f is the Indexing function, $\mathsf{Q}(f_{\mathsf{sab}}) = \Theta(\mathsf{fbs}(f))$, ruling out the possibility that $\mathsf{Q}(f_{\mathsf{sab}}) = \Theta(\sqrt{\mathsf{fbs}(f)})$ for all f.

1 Introduction

Given a Boolean function $f : \{0,1\}^n \to \{0,1\}$, the goal in the standard query complexity model is to compute $f(x)$ on an unknown input $x \in \{0,1\}^n$ using as few queries to x as possible. One can also consider the following distinguishing problem: given $x \in f^{-1}(0)$ and $y \in f^{-1}(1)$, output an index $i \in [n]$ such that $x_i \neq y_i$. This task can be formulated as follows: consider an arbitrary $x \in f^{-1}(0)$, an arbitrary $y \in f^{-1}(1)$, and then either all indices where x and y differ are replaced by the symbol $*$, or all such indices are replaced by the symbol †. The goal of an algorithm is to identify which of these is the case, with query access to this "sabotaged" input. A formal description of this task is given below.

*IRIF - CNRS, Paris, France ajcornelissen@outlook.com

†University of Liverpool, UK mande@liverpool.ac.uk

‡Eindhoven University of Technology (TU/e) & Centrum Wiskunde en Informatica (QuSoft), The Netherlands patrofied@gmail.com. This work was partially done while the author was affiliated to Utrecht University.

