

Quantum Sieving for Code-Based Cryptanalysis and Its Limitations for ISD

Lynn Engelberts[1,2], Simona Etinski[1], and Johanna Loyer[1]
firstname.lastname@cwi.nl

[1] CWI, The Netherlands
[2] QuSoft, The Netherlands

arXiv:2408.16458v2 [quant-ph] 24 Dec 2024

Abstract. Sieving using near-neighbor search techniques is a well-known method in lattice-based cryptanalysis, yielding the current best runtime for the shortest vector problem in both the classical [BDGL16] and quantum [BCSS23] setting. Recently, sieving has also become an important tool in code-based cryptanalysis. Specifically, using a sieving subroutine, [GJN23, DEEK24] presented a variant of the information-set decoding (ISD) framework, which is commonly used for attacking cryptographically relevant instances of the decoding problem. The resulting sieving-based ISD framework yields complexities close to the best-performing classical algorithms for the decoding problem such as [BJMM12, BM18]. It is therefore natural to ask how well quantum versions perform. In this work, we introduce the first quantum algorithms for code sieving by designing quantum variants of the aforementioned sieving subroutine. In particular, using quantum-walk techniques, we provide a speed-up over the best known classical algorithm from [DEEK24] and over a variant using Grover's algorithm. Our quantum-walk algorithm exploits the structure of the underlying search problem by adding a layer of locality-sensitive filtering, inspired by the quantum-walk algorithm for lattice sieving from [CL21]. We complement our asymptotic analysis of the quantum algorithms with numerical results, and observe that our quantum speed-ups for code sieving behave similarly as those observed in lattice sieving. In addition, we show that a natural quantum analog of the sieving-based ISD framework does not provide any speed-up over the first presented quantum ISD algorithm [Ber10]. Our analysis highlights that the framework should be adapted in order to outperform the state-of-the-art of quantum ISD algorithms [KT17, Kir18].

Keywords. Quantum cryptanalysis, Quantum walks, Near-neighbor search, Code sieving, Decoding problem, Information-set decoding

1 Introduction

A fundamental problem in code-based cryptography is the decoding problem: given a linear code $\mathcal{C}$, find a codeword $\mathbf{x}_c \in \mathcal{C}$ of (small) fixed weight w.[3] The decoding problem is NP-hard in the worst case [BMvT78]. More important for cryptographic purposes, it is known that w can be chosen to guarantee the existence of exactly one solution on average, which gives us the so-called *unique decoding regime*. In this regime, the decoding problem is believed to be hard for a random instance of the problem. In particular, all known algorithms for attacking a random instance of this problem run in time and memory exponential in the input size. The best generic attacks[4] belong to the so-called *information-set decoding* (ISD) framework.

The ISD framework was originally introduced in the work of Prange [Pra62], and further improved using various techniques, including the meet-in-the-middle approach and its generalizations [Ste88, Dum91,SS81], representation techniques [MMT11,BJMM12], near-neighbor search techniques [MO15, Car20], and their combinations. Some of these techniques were adapted to the quantum setting [Ber10, KT17, Kir18]. To find the solution to the decoding problem, current ISD algorithms search for many partial solutions (by solving an instance of the decoding problem in a smaller dimension), and then check if any of those yields a solution to the original problem.

[3] This problem is called the codeword-finding problem in [DEEK24], and can be seen as a homogeneous version of the well-known syndrome decoding problem.

[4] For certain parameter regimes, the so-called statistical decoding attacks (also known as dual attacks in the lattice literature) are more efficient. As we are not particularly interested in a specific parameter regime, we will only consider attacks in the ISD framework.

