

2022–2025

arXiv:2409.04550v4 [quant-ph] 26 Sep 2025

Solving Free Fermion Problems on a Quantum Computer

Maarten Stroeks,[1,2,*] Daan Lenterman,[3] Barbara M. Terhal,[1,2] and Yaroslav Herasymenko[2,4,†]

[1] *QuTech, TU Delft, Lorentzweg 1, 2628 CJ Delft, The Netherlands*
[2] *Delft Institute of Applied Mathematics, TU Delft, 2628 CD Delft, The Netherlands*
[3] *Department of Physics, ETH Zürich, CH-8093 Zürich, Switzerland*
[4] *QuSoft and CWI, Science Park 123, 1098 XG Amsterdam, The Netherlands*

Simulating noninteracting fermion systems is a common task in computational many-body physics. In absence of translational symmetries, modeling free fermions on N modes usually requires poly(N) computational resources. While often moderate, these costs can be prohibitive in practice when large systems are considered. We present several free-fermion problems that can be solved by a quantum algorithm with substantially reduced computational costs. The memory costs are exponentially improved, poly $\log(N)$. The runtime improvement, compared to the best known classical algorithms, is either exponential or significantly polynomial, depending on the geometry of the problem. The simulation of free-fermion dynamics belongs to the BQP-hard complexity class. This implies (under standard assumptions) that our algorithm yields an exponential speedup for *any* classical algorithm at least for some geometries. The key technique in our algorithm is the block-encoding of objects such as correlation matrices and Green's functions into a unitary. We demonstrate how such unitaries can be efficiently realized as quantum circuits, in the context of dynamics and thermal states of tight-binding Hamiltonians. The special cases of disordered and inhomogeneous lattices, as well as large non-lattice graphs, are presented in detail. Finally, we show that our simulation algorithm generalizes to other promising targets, including free boson systems.

I. INTRODUCTION AND BACKGROUND

Quantum many-body dynamics can be naturally simulated by a quantum computer [1], enabling its applications in condensed matter and quantum chemistry. For a system of size N, standard quantum algorithms use poly(N) resources for such simulations. It implies an exponential advantage over classical methods, when dealing with a generic many-body system. Such a general advantage may not hold in special cases of interest, such as the modeling of free fermions, where the best classical algorithms also have poly(N) cost [2–4]. This classical efficiency has been key to many successes of computational physics, as free fermions model a variety of systems in condensed matter and quantum chemistry; they have also been used in computational strategies for solving interacting fermion systems, using mean-field (Hartree-Fock), perturbative methods or dynamical mean-field theory. Nonetheless, in the practical simulations of noninteracting fermions, even the most efficient numerical methods become too expensive for large systems. This motivates the key question of this work: can a quantum computer boost free-fermion simulations beyond what can be done classically? We answer this question in the affirmative, presenting quantum algorithms with an exponential speedup and memory compression for several free-fermion problems.

To appreciate the value of such an exponential reduction, consider numerical simulations of free-fermion models of materials and interfaces for quantum transport [5, 6]. These can become prohibitive when involving more than $N = 10^9$ modes, which is of practical interest when simulating 3-dimensional lattice models. Upon compression, a system of 10^9 sites can be described by $n = 30$ qubits. Larger systems of practical interest could still be accessed with moderately sized quantum computers. Indeed, even simulating one mole ($N \simeq 10^{24}$) of fermionic modes requires fewer than $n = 80$ qubits in compressed form. This opens the door to modeling free fermions near the thermodynamic limit — a desired but often challenging goal.

Our result is based on an understanding of the reduced classical complexity of free-fermion systems. As an inspiration, we used the fact that the matchgate computations and the dynamics of free fermion problems on $N = 2^n$ modes can be simulated in compressed form, using $O(n)$ *space* on a quantum computer [7–11]. In this work, we go beyond these memory compression results to identify free fermion problems that also permit an exponentially improved, poly(n) quantum *run-time*. Our key idea is to represent the relevant 2^n-sized object—such as the correlation matrix or a Green's function of a free-fermion state—as a block of an n-qubit unitary. This unitary can be given as an efficient quantum circuit; we provide explicit construction methods by leveraging the modern quantum algorithm toolbox of block-encoding manipulations [12–16]. In particular, we show how to construct the desired unitary for free-fermion states arising from time dynamics or thermal equilibrium. Given block-encodings of the aforementioned objects into a circuit, we show how to accurately extract various physical quantities for a state, including the occupation number on a given site, or energy density across the entire system. We analyze the application of our methods to free-fermion models on d-dimensional lattices and expander graphs. For the particular case of d-dimensional lattices,



* m.e.h.m.stroeks@tudelft.nl
† yaroslav@cwi.nl