

2021–2026

arXiv:2411.00082v2 [quant-ph] 6 Jun 2025

Testing and learning structured quantum Hamiltonians

Srinivasan Arunachalam
IBM Quantum
Almaden Research Center, CA, USA
Srinivasan.Arunachalam@ibm.com

Arkopal Dutt
IBM Quantum
Cambridge, MA, USA
arkopal@ibm.com

Francisco Escudero Gutiérrez
Qusoft and CWI
Amsterdam, Netherlands
feg@cwi.nl

Abstract

We consider the problems of testing and learning an n-qubit Hamiltonian $H = \sum_x \lambda_x \sigma_x$ expressed in its Pauli basis, from queries to its evolution operator $U = e^{-iHt}$. To this end, we prove the following results.

1. **Testing**: We give a *tolerant* testing protocol to decide if a Hamiltonian is ε_1-close to k-local or ε_2-far from k-local in the ℓ_2 norm of the coefficients, with $O(1/(\varepsilon_2-\varepsilon_1)^4)$ queries, thereby solving two open questions posed in a recent work by Bluhm, Caro and Oufkir [BCO24a]. We give a protocol for testing whether a Hamiltonian is ε_1-close to being s-sparse or ε_2-far from being s-sparse in the ℓ_2 norm of the coefficients, with $O(s^6/(\varepsilon_2^2-\varepsilon_1^2)^6)$ queries.
2. **Learning**: We give a protocol to ε-learn unstructured Hamiltonian in the ℓ_∞ norm of the coefficients with $O(1/\varepsilon^4)$ queries. Combining this with the non-commutative Bohnenblust-Hille inequality, we obtain an algorithm for learning k-local Hamiltonians in ℓ_2 norm of the coefficients that only uses $O(\exp(k^2 + k\log(1/\varepsilon)))$ queries. For Hamiltonians that are s-sparse in the Pauli basis, we can learn them in the ℓ_2 norm with $O(s^2/\varepsilon^4)$ queries.
3. **Learning without quantum memory**: The learning results stated above have no dependence on the system size n, but require n-qubit quantum memory. We give subroutines that allow us to reproduce all the above learning results without quantum memory; squaring the query complexity and paying a $(\log n)$-factor in the local case and an n-factor in the sparse case.
4. **Testing without quantum memory**: We give a new subroutine called *Pauli hashing*, which allows one to tolerantly test s-sparse Hamiltonians in ℓ_2 norm using $\tilde{O}(s^{14}/(\varepsilon_2^2-\varepsilon_1^2)^{18})$ query complexity. A key ingredient is showing that s-sparse Pauli channels can be tested in a tolerant fashion as being ε_1-close to being s-sparse or ε_2-far under the diamond norm, using $\tilde{O}(s^2/(\varepsilon_2-\varepsilon_1)^6)$ queries via Pauli hashing.

In order to prove these results, we prove new structural theorems for local Hamiltonians, sparse Pauli channels and sparse Hamiltonians. We complement our learning algorithms with lower bounds that are polynomially weaker. Furthermore, our algorithms use short time evolutions and do not assume prior knowledge of the terms on which the Pauli spectrum is supported on, i.e., we do not require prior knowledge about the *support* of the Hamiltonian terms.

