

arXiv:2411.03648v1 [quant-ph] 6 Nov 2024

Quantum Programmable Reflections

Eddie Schoute*[1,3], Dmitry Grinko[2,4,5], Yiğit Subaşı†[1], and Tyler Volkoff[2]

[1]Computer, Computational and Statistical Sciences Division, Los Alamos National Laboratory, Los Alamos, NM, USA
[2]Theoretical Division, Los Alamos National Laboratory, Los Alamos, NM, USA
[3]IBM Quantum, IBM Research, Cambridge, MA, USA
[4]Institute for Logic, Language and Computation, University of Amsterdam, Amsterdam, NL
[5]QuSoft, Amsterdam, NL

Abstract

Similar to a classical processor, which is an algorithm for reading a program and executing its instructions on input data, a universal programmable quantum processor is a fixed quantum channel that reads a quantum program $|\psi_U\rangle$ that causes the processor to approximately apply an arbitrary unitary U to a quantum data register. The present work focuses on a class of simple programmable quantum processors for implementing reflection operators, i.e. $U = e^{i\pi|\psi\rangle\langle\psi|}$ for an arbitrary pure state $|\psi\rangle$ of finite dimension d. Unlike quantum programs that assume query access to U, our program takes the form of independent copies of the state to be reflected about $|\psi_U\rangle = |\psi\rangle^{\otimes n}$. We then identify the worst-case optimal algorithm among all processors of the form $\mathrm{tr}_{\mathrm{Program}}[V(|\phi\rangle\langle\phi|\otimes(|\psi\rangle\langle\psi|)^{\otimes n})V^\dagger]$ where the algorithm V is a unitary linear combination of permutations. By generalizing these algorithms to processors for arbitrary-angle rotations, $e^{i\alpha|\psi\rangle\langle\psi|}$ for $\alpha \in \mathbb{R}$, we give a construction for a universal programmable processor with better scaling in d. For programming reflections, we obtain a tight analytical lower bound on the program dimension by bounding the Holevo information of an ensemble of reflections applied to an entangled probe state. The lower bound makes use of a block decomposition of the uniform ensemble of reflected states with respect to irreps of the partially transposed permutation matrix algebra, and two representation-theoretic conjectures based on extensive numerical evidence. Finally, we observe that programming the submanifold of reflections obeys a conjecture by Yang, Renner, and Chiribella [YRC20] with the dependence on the dimension being much weaker compared to universal programming.

*eddie.schoute@ibm.com
†ysubasi@lanl.gov

