



arXiv:2502.08721v2 [quant-ph] 4 Aug 2025

Complement Sampling: Provable, Verifiable and NISQable Quantum Advantage in Sample Complexity

Marcello Benedetti[1], Harry Buhrman[1,2,3], and Jordi Weggemans[2,4,*]

[1]Quantinuum, London, United Kingdom
[2]QuSoft, The Netherlands
[3]University of Amsterdam, Amsterdam, The Netherlands
[4]CWI, The Netherlands
[*]jrw@cwi.nl

August 4, 2025

Abstract

Consider a fixed universe of $N = 2^n$ elements and the uniform distribution over elements of some subset of size K. Given samples from this distribution, the task of complement sampling is to provide a sample from the complementary subset. We give a simple quantum algorithm that uses only a *single* quantum sample—a single copy of the uniform superposition over elements of the subset. When $K = N/2$, we show that the quantum algorithm succeeds with probability 1, whereas classically $\Theta(N)$ samples are required to succeed with bounded probability of error. This shows that in a sample-to-sample setting, quantum computation can achieve the largest possible separation over classical computation. Moreover, we show that the same bound can be lifted to prove average-case hardness. It follows that under the assumption of the existence of one-way functions, complement sampling gives provable, verifiable and NISQable quantum advantage in a sample complexity setting.

Contents

1 Introduction **2**
1.1 Quantum advantage in complement sampling . . . 2
1.2 The construction and proof ideas . . . 6
1.3 Discussion and future work . . . 8

2 Complement sampling using quantum samples **9**
2.1 Aaronson, Atia and Susskind's construction . . . 9
2.2 A perfect swapper for subsets of cardinality $K = N/2$ . . . 11
2.3 Impossibility of a perfect swapper for $K \neq N/2$ . . . 12
2.4 Probabilistic zero-error algorithm for any subset . . . 14
2.5 Zero error: optimality, auxiliary qubits and multiple samples . . . 16

3 Classical samples: lower and upper bounds **19**
3.1 Index query model . . . 19
3.2 Exact sample complexity bounds . . . 21
3.3 Average-case lower bounds . . . 22
3.4 Hardness for strong pseudorandom subsets . . . 23
3.5 Circuit lower bounds for uniform samplers . . . 25

4 Circuit complexity and distinguishability of subset states **26**
4.1 Warm-up: exact case . . . 26
4.2 Approximate case . . . 27