



Quantum Catalytic Space

Harry Buhrman
Quantinuum London & QuSoft
h.m.buhrman@uva.nl

Marten Folkertsma *
CWI & QuSoft
mjf@cwi.nl

Ian Mertz †
Charles University
iwmertz@iuuk.mff.cuni.cz

Florian Speelman ‡
University of Amsterdam & QuSoft
f.speelman@uva.nl

Sergii Strelchuk §
University of Oxford
sergii.strelchuk@cs.ox.ac.uk

Sathyawageeswar Subramanian ¶
University of Cambridge
ss2310@cam.ac.uk

Quinten Tupker ‖
CWI & QuSoft
qmtupker@gmail.com

June 23, 2025

arXiv:2506.16324v1 [quant-ph] 19 Jun 2025

Abstract

Space complexity is a key field of study in theoretical computer science. In the quantum setting there are clear motivations to understand the power of space-restricted computation, as qubits are an especially precious and limited resource.

Recently, a new branch of space-bounded complexity called catalytic computing has shown that reusing space is a very powerful computational resource, especially for subroutines that incur little to no space overhead. While quantum catalysis in an information theoretic context, and the power of "dirty" qubits for quantum computation, has been studied over the years, these models are generally not suitable for use in quantum space-bounded algorithms, as they either rely on specific catalytic states or destroy the memory being borrowed.

We define the notion of catalytic computing in the quantum setting and show a number of initial results about the model. First, we show that quantum catalytic logspace can always be computed quantumly in polynomial time; the classical analogue of this is the largest open question in catalytic computing. This also allows quantum catalytic space to be defined in an equivalent way with respect to circuits instead of Turing machines. We also prove that quantum catalytic logspace can simulate log-depth threshold circuits, a class which is known to contain (and believed to strictly contain) quantum logspace, thus showcasing the power of quantum catalytic space. Finally we show that both unitary quantum catalytic logspace and classical catalytic logspace can be simulated in the one-clean qubit model.

*Supported by the Dutch Ministry of Economic Affairs and Climate Policy (EZK), as part of the Quantum Delta NL programme.

†Supported by the Grant Agency of the Czech Republic under the grant agreement no. 24-10306S and by the Center for Foundations of Contemporary Computer Science (Charles Univ. project UNCE 24/SCI/008).

‡Supported by the Dutch Ministry of Economic Affairs and Climate Policy (EZK), as part of the Quantum Delta NL program, and the project Divide and Quantum 'D&Q' NWA.1389.20.241 of the program 'NWA-ORC', which is partly funded by the Dutch Research Council (NWO)

§Supported by a Royal Society University Research Fellowship and the EPSRC (RoaRQ), Investigation 005 [grantreference EP/W032635/1].

¶Supported by a Royal Commission for the Exhibition of 1851 Research Fellowship.

‖Supported by the Dutch National Growth Fund (NGF), as part of the Quantum Delta NL program.