



Hidden shift problem for complex functions

Serge Adonsou[1], Peter Bruin[2], Maris Ozols[3,4], Joppe Stokvis[2,3]

[1]Department of Mathematics and Statistics, University of Guelph, Canada
[2]Mathematical Institute, Leiden University, Netherlands
[3]QuSoft, Amsterdam, Netherlands
[4]Institute for Logic, Language and Computation, and Korteweg-de Vries Institute for Mathematics, University of Amsterdam, Netherlands
Email addresses: sadonsou@uoguelph.ca, p.j.bruin@math.leidenuniv.nl, marozols@gmail.com, j.a.stokvis@math.leidenuniv.nl

July 28, 2025

arXiv:2507.19440v1 [quant-ph] 25 Jul 2025

Abstract

We study quantum algorithms for the hidden shift problem of complex scalar- and vector-valued functions on finite abelian groups. Given oracle access to a shifted function and the Fourier transform of the unshifted function, the goal is to find the hidden shift. We analyze the success probability of our algorithms when using a constant number of queries. For bent functions, they succeed with probability 1, while for arbitrary functions the success probability depends on the 'bentness' of the function.

Contents

1 Introduction **2**
1.1 Precise problem statement . . . 3
1.2 Our results . . . 4

2 Preliminaries **5**
2.1 Quantum circuits and complexity . . . 5
2.2 Group characters and Fourier transform . . . 6
2.3 The quantum Fourier transform operator . . . 7

3 Exact algorithm for bent functions **7**
3.1 Classical algorithm . . . 8
3.2 Quantum algorithm . . . 8

4 Approximate algorithms for bent-like functions **10**
4.1 First generalization: $(R, \hat{r})$-bounded functions . . . 10
4.2 Second generalization: more parameters . . . 12
4.3 Example: characters . . . 13
4.4 Symmetry of the algorithm . . . 14

5 Multidimensional bent functions **15**
5.1 Exact algorithm . . . 16
5.2 Approximate algorithm . . . 16

6 One-register approach **18**
6.1 Oracles . . . 19
6.2 Approximate algorithm . . . 19
6.3 Lower bounds for the success probability . . . 24

7 Discussion **26**

A Error analysis **29**

