



The Compressed Oracle is a Worthy (Multiplicative) Adversary

Stacey Jeffery*[1] and Sebastian Zur†[2]

[1]QuSoft, CWI & University of Amsterdam, the Netherlands
[2]IRIF & CNRS, France

September 10, 2025

arXiv:2509.07876v1 [quant-ph] 9 Sep 2025

Abstract

The compressed oracle technique, introduced in the context of quantum cryptanalysis, is the latest method for proving quantum query lower bounds, and has had an impressive number of applications since its introduction, due in part to the ease of importing classical lower bound intuition into the quantum setting via this method. Previously, the main quantum query lower bound methods were the polynomial method, the adversary method, and the multiplicative adversary method, and their relative powers were well understood. In this work, we situate the compressed oracle technique within this established landscape, by showing that it is a special case of the multiplicative adversary method. To accomplish this, we introduce a simplified restriction of the multiplicative adversary method, the *MLADV* method, that remains powerful enough to capture the polynomial method and exhibit a strong direct product theorem, but is much simpler to reason about. We show that the compressed oracle technique is also captured by the MLADV method. This might make the MLADV method a promising direction in the current quest to extend the compressed oracle technique to non-product distributions.

1 Introduction

Proving quantum query lower bounds is essential to understanding the limitations of quantum computers. In the *bounded-error quantum query model*, an algorithm for a problem F receives its input – typically a string in $[M]^N$ for some integers M and N – encoded as a function $f : [N] \to [M]$, accessible only through queries. The algorithm may alternate such queries with arbitrary quantum operations, and it must produce the correct output on every input with probability at least $2/3$. The *bounded-error quantum query complexity* of F, denoted $Q(\mathsf{F})$, is the minimum number of queries needed by any such algorithm. Allowing some small probability of error makes this a practical model of computation, and lower bounds on the query complexity of an algorithm are also lower bounds on the total number of steps the algorithm must make.

The first technique for proving quantum query lower bounds was the *polynomial method* [BBC+01], which showed that the acceptance probability of a quantum algorithm can be represented by a low-degree polynomial. In this method, one lower bounds the quantum query complexity of F by lower bounding its *approximate degree* $\widetilde{\deg}(\mathsf{F})$, by proving a lower bound on the degree of any polynomial with certain properties that must be satisfied by any successful algorithm. Later, the *adversary method* was introduced in [Amb02] and generalized to its full version in [HLŠ07]. Letting $\mathsf{ADV}^{\pm}(\mathsf{F})$ denote the best possible lower bound on the quantum query complexity of F that one can prove using the adversary method, it was later shown that this quantity is equal, up to constants, to $Q(\mathsf{F})$, making this a very powerful method. In contrast, there are problems for which the polynomial method is not able to prove tight lower bounds, since $\widetilde{\deg}(\mathsf{F}) = o(Q(\mathsf{F}))$ [ABDK16]. However, the polynomial method has

*This work is supported by ERC STG grant 101040624-ASC-Q and NWO Klein project number OCENW.Klein.061. SJ is a CIFAR Fellow in the Quantum Information Science Program.

†The majority of this work was conducted while SZ was affiliated with CWI & QuSoft, the Netherlands.