

2021–2025

arXiv:2510.05393v2 [quant-ph] 14 Oct 2025

On Limits on the Provable Consequences of Quantum Pseudorandomness

Samuel Bouaziz--Ermann[1], Minki Hhan*[2], Garazi Muguruza[3], Quoc-Huy Vu[4]

[1]Sorbonne Université, CNRS, LIP6, France
samuel.bouaziz-ermann@lip6.fr
[2]The University of Texas at Austin, Texas, USA
minki.hhan@austin.utexas.edu
[3]MNS & QuSoft, University of Amsterdam
g.muguruzalasa@uva.nl
[4]De Vinci Higher Education, De Vinci Research Center, Paris, France
quoc.huy.vu@ens.fr

Abstract

There are various notions of quantum pseudorandomness, such as pseudorandom unitaries (PRUs), pseudorandom state generators (PRSGs) and pseudorandom function-like state generators (PRSFGs). Unlike the different notions of classical pseudorandomness, which are known to be existentially equivalent to each other, the relation between quantum pseudorandomness has yet to be fully established.

We present some evidence suggesting that some quantum pseudorandomness is unlikely to be constructed from the others, or at least is hard to construct unless some conjectures are false. This indicates that quantum pseudorandomness could behave quite differently from classical pseudorandomness. We study new oracle worlds where one quantum pseudorandomness exists but another pseudorandomness does not under some assumptions or constraints, and provide potential directions to achieve the full black-box separation. More precisely:

- We give a unitary oracle relative to which PRFSGs exist but PRUs without using ancilla do not. This can be extended to the general PRUs if a structural property of the PRU algorithm holds.
- Assuming an isoperimetric inequality-style conjecture, we show a unitary oracle world where log-length output PRFSGs exist but proving the existence of quantum-computable pseudorandom generators (QPRGs) with negligible correctness error is as hard as proving that $\mathsf{BQP} \neq \mathsf{QCMA}$. This result suggests that the inverse-polynomial error in the state of the art construction of QPRGs from log-length PRSGs is inherent.
- Assuming the same conjecture, we prove that some natural way of constructing super-log-length output PRSGs from log-length output PRFSGs is impossible. This partly complements the known hardness of shrinking the PRSG output lengths. Along the way, we also discuss other potential approaches to extend the PRSG output lengths.

All our worlds are based on (variants of) oracles that output Haar random quantum states for each bit string, which can be viewed as a quantum version of the random oracle model, where output strings are replaced by quantum states.

Our results highlight technical difficulties when dealing with ancillary registers, measurements, and adaptivity in the quantum setting. As one of our key technical tools, we show an intriguing *gentle* behavior of intermediate measurements in algorithms producing outcome states with high purity, which may be of independent interest.

*This work was done in part while the second author was affiliated at KIAS, Korea.

