





An Improved Quantum Algorithm for 3-Tuple Lattice Sieving

Lynn Engelberts[*] Yanlin Chen[†] Amin Shiraz Gilani[‡] Maya-Iggy van Hoof[§]
Stacey Jeffery[¶] Ronald de Wolf[‖]

December 3, 2025

arXiv:2510.08473v2 [quant-ph] 2 Dec 2025

Abstract

The assumed hardness of the Shortest Vector Problem in high-dimensional lattices is one of the cornerstones of post-quantum cryptography. The fastest known heuristic attacks on SVP are via so-called sieving methods. While these still take exponential time in the dimension d, they are significantly faster than non-heuristic approaches and their heuristic assumptions are verified by extensive experiments. k-Tuple sieving is an iterative method where each iteration takes as input a large number of lattice vectors of a certain norm, and produces an equal number of lattice vectors of slightly smaller norm, by taking sums and differences of k of the input vectors. Iterating these "sieving steps" sufficiently many times produces a short lattice vector. The fastest attacks (both classical and quantum) are for $k = 2$, but taking larger k reduces the amount of memory required for the attack. In this paper we improve the quantum time complexity of 3-tuple sieving from $2^{0.3098d}$ to $2^{0.2846d}$, using a two-level amplitude amplification aided by a preprocessing step that associates the given lattice vectors with nearby "center points" to focus the search on the neighborhoods of these center points. Our algorithm uses $2^{0.1887d}$ classical bits and QCRAM bits, and $2^{o(d)}$ qubits. This is the fastest known quantum algorithm for SVP when total memory is limited to $2^{0.1887d}$.

[*]QuSoft and CWI, the Netherlands. Supported by the Dutch National Growth Fund (NGF), as part of the Quantum Delta NL program. lynn.engelberts@cwi.nl

[†]QuICS and University of Maryland, United States. Most of this work was completed while the author was at QuSoft and CWI. yanlin@umd.edu

[‡]QuICS and University of Maryland, United States. Partially supported by the DOE ASCR Quantum Testbed Pathfinder program (awards DE-SC0019040 and DE-SC0024220). asgilani@umd.edu

[§]Horst Görtz Institute for IT-Security, Ruhr University Bochum, Bochum, Germany. Partially supported by the Deutsche Forschungsgemeinschaft (DFG, German Research Foundation) under Germany's Excellence Strategy-EXC 2092 CASA-390781972 "Cyber Security in the Age of Large-Scale Adversaries". iggy.hoof@ruhr-uni-bochum.de

[¶]QuSoft, CWI and University of Amsterdam, the Netherlands. Partially supported by the European Union (ERC, ASC-Q, 101040624). SJ is a CIFAR Fellow in the Quantum Information Science Program. jeffery@cwi.nl

[‖]QuSoft, CWI and University of Amsterdam, the Netherlands. Partially supported by the Dutch Research Council (NWO) through Gravitation-grant Quantum Software Consortium, 024.003.037. rdewolf@cwi.nl

