



Unconditional and exponentially large violation of classicality

Marcello Benedetti*[1], Gabriel Marin-Sanchez[1], Jordi Weggemans[1], Matthias Rosenkranz[1], and Harry Buhrman†[1,2]

[1]Quantinuum, London, United Kingdom
[2]University of Amsterdam & QuSoft, The Netherlands

arXiv:2511.11008v1 [quant-ph] 14 Nov 2025

November 17, 2025

Abstract

Testing the predictions of quantum mechanics has been one of the main experimental endeavors for decades [1–4]. Recent advancements in technology led to a number of demonstrations [5–9] which test non-classicality via specific computational tasks. Limitations of these experiments include dependence on complexity theory assumptions [10], susceptibility to hardware noise [11] and inefficient verification [12, 13], raising questions about their scalability. We propose to test non-classicality using a game based on complement sampling [14], an efficiently verifiable problem that achieves the largest possible separation between quantum and classical computation when both input and output represent samples from probability distributions. When restricting the input to instances inspired by the Bernstein-Vazirani problem [15], our game admits an exponentially large violation of classicality without relying on computational hardness assumptions. We execute the game on Quantinuum System Model H2 trapped-ion quantum computers, with experiments consisting of thousands of different circuits on up to 55 qubits. The observed scores can be explained by a systematic adoption of a quantum strategy, further corroborating the quantum nature of the hardware in an efficient and scalable way.

Introduction. A prominent approach to validate quantum mechanics' predictions is by examining violations of Bell inequalities [16]. Such experiments can be formulated as collaborative games with two players [17], often called non-local games. At each round, the referee sends a question to each player. The players can only see their own question, to which they provide an answer. A referee evaluates a function of both answers and questions to decide whether the round has been won. Depending on the resources and strategies allowed (e.g. classical, quantum, and non-signaling) the output statistics attain different maximal values.

Tests on quantum mechanics can also be designed around computational tasks, where complexity theory provides the foundation to build upon [18]. This approach has gained traction thanks to the recent technological progress towards some of the challenges of building quantum computers. However, since error-corrected large-scale quantum computers remain inaccessible at the moment, researchers have focused on random circuit sampling (RCS), a task designed for noisy hardware. Under noise models aligned with existing quantum technologies, numerical simulations suggest that achieving a polynomial quantum speedup in RCS is restricted, at best, to circuits of few hundred qubits and depths up to one hundred [11]. Beyond 50 qubits, even if the output of the circuit still carries a signal despite the noise, it becomes very hard to verify the results due to the classical computational hardness of this. RCS suffers from either exponential classical-time verification [13], as it requires noiseless classical simulation of the circuits, or exponential sample complexity [12], due to the output distributions having high

*marcello.benedetti@quantinuum.com
†harry.buhrman@quantinuum.com