

arXiv:1504.05255v4 [cs.CR] 1 Jun 2016

Semantic Security and Indistinguishability in the Quantum World

June 2, 2016[⋆]

Tommaso Gagliardoni[1], Andreas Hülsing[2], and Christian Schaffner[3,4,5]

[1] CASED, Technische Universität Darmstadt, Germany
tommaso@gagliardoni.net
[2] TU Eindhoven, The Netherlands
andreas@huelsing.net
[3] Institute for Logic, Language and Compuation (ILLC), University of Amsterdam, The Netherlands
c.schaffner@uva.nl
[4] Centrum Wiskunde & Informatica (CWI) Amsterdam, The Netherlands
[5] QuSoft, The Netherlands

Abstract. At CRYPTO 2013, Boneh and Zhandry initiated the study of quantum-secure encryption. They proposed first indistinguishability definitions for the quantum world where the actual indistinguishability only holds for classical messages, and they provide arguments why it might be hard to achieve a stronger notion. In this work, we show that stronger notions are achievable, where the indistinguishability holds for quantum superpositions of messages. We investigate exhaustively the possibilities and subtle differences in defining such a quantum indistinguishability notion for symmetric-key encryption schemes. We justify our stronger definition by showing its equivalence to novel quantum semantic-security notions that we introduce. Furthermore, we show that our new security definitions cannot be achieved by a large class of ciphers – those which are quasi-preserving the message length. On the other hand, we provide a secure construction based on quantum-resistant pseudorandom permutations; this construction can be used as a generic transformation for turning a large class of encryption schemes into quantum indistinguishable and hence quantum semantically secure ones. Moreover, our construction is the first completely classical encryption scheme shown to be secure against an even stronger notion of indistinguishability, which was previously known to be achievable only by using quantum messages and arbitrary quantum encryption circuits.

1 Introduction

Quantum computers [NC00] threaten many cryptographic schemes. By using Shor's algorithm [Sho94] and its variants [Wat01], an adversary in possession of a quantum computer can break the security of every scheme based on factorization and discrete logarithms, including RSA, ElGamal, elliptic-curve primitives and many others. Moreover, longer keys and output lengths are required in order to

⋆ An extended abstract of this work appears in the proceedings of CRYPTO 2016. This is the full version.