

Quantum Query Algorithms are Completely Bounded Forms

Srinivasan Arunachalam* Jop Briët† Carlos Palazuelos‡

arXiv:1711.07285v3 [quant-ph] 10 May 2022

Abstract

We prove a characterization of t-query quantum algorithms in terms of the unit ball of a space of degree-$2t$ polynomials. Based on this, we obtain a refined notion of approximate polynomial degree that equals the quantum query complexity, answering a question of Aaronson et al. (CCC'16). Our proof is based on a fundamental result of Christensen and Sinclair (*J. Funct. Anal.*, 1987) that generalizes the well-known Stinespring representation for quantum channels to multilinear forms. Using our characterization, we show that many polynomials of degree four are far from those coming from two-query quantum algorithms. We also give a simple and short proof of one of the results of Aaronson et al. showing an equivalence between one-query quantum algorithms and bounded quadratic polynomials.

Revision note: A mistake was found in the proof of the second result on degree-4 polynomials far from 2-query quantum algorithms. An explanation of the issue, a corrected proof and stronger examples are presented in work of Escudero Gutiérrez and the second author.

1 Introduction

In the black-box model of quantum computation one is given access to a unitary operation, usually referred to as an oracle, that allows one to probe the bits of an unknown binary string $x \in \{-1,1\}^n$ in superposition. Promised that x lies in a subset $D \subseteq \{-1,1\}^n$, the goal in this model is to learn some property of x given by a Boolean function $f : D \to \{-1,1\}$, when only given access to x through the oracle. An application of the oracle is usually referred to as a *query*. The bounded-error quantum query complexity of f, denoted $Q_\varepsilon(f)$, is the minimal number of queries a quantum algorithm must make on the worst-case input $x \in D$ to compute $f(x)$ with probability at least $1-\varepsilon$, where $\varepsilon \in (0,1/2)$ is usually some fixed but arbitrary positive constant.

Many of the best-known quantum algorithms are naturally captured by this model. A few examples of partial functions whose quantum query complexity is exponentially smaller than their classical counterpart (the decision-tree complexity) are period finding [Sho97], Simon's problem [Sim97] and Forrelation [AA15]. Famous problems related to total functions that admit polynomial quantum speed-ups include unstructured search [Gro96], element distinctness [Amb07]

*QuSoft, CWI and University of Amsterdam, the Netherlands. Supported by ERC Consolidator Grant QPROGRESS. E-mail: arunacha@cwi.nl

†CWI, QuSoft. Supported by a VENI grant and the Gravitation-grant NETWORKS-024.002.003 from the Netherlands Organisation for Scientific Research (NWO). E-mail: j.briet@cwi.nl

‡Facultad de C.C. Matematicas, UCM. Instituto de Ciencias Matematicas, Madrid Spain. Supported by the Ramon y Cajal program (RYC-2012-10449), the Spanish MINECO MTM2014-54240-P, Comunidad de Madrid (QUITEMAD+ Project S2013/ICE-2801) and ICMAT Severo Ochoa Grant No. SEV-2015-0554. E-mail: carlospalazuelos@mat.ucm.es