

Experimental Demonstration of Quantum Fully Homomorphic Encryption with Application in a Two-Party Secure Protocol

W.K. Tham,[1,2,*] Hugo Ferretti,[1,2] Kent Bonsma-Fisher,[1,2] Aharon Brodutch,[1,2,3]
Barry C. Sanders,[4,5,6] Aephraim M. Steinberg,[1,2] and Stacey Jeffery[7]

[1] *Department of Physics, University of Toronto, 60 St George St, Toronto, Ontario, M5S 1A7, Canada*
[2] *Center for Quantum Information and Quantum Control, University of Toronto, 60 St George St, Toronto, Ontario, M5S 1A7, Canada*
[3] *The Edward S. Rogers Department of Electrical and Computer Engineering, University of Toronto, 10 Kings College Road, Toronto, Ontario M5S 3G4, Canada*
[4] *Institute for Quantum Science and Technology, University of Calgary, Alberta T2N 1N4, Canada*
[5] *Institute for Quantum Information and Matter, California Institute of Technology, Pasadena, California 91125, USA*
[6] *Program in Quantum Information Science, Canadian Institute for Advanced Research, Toronto, Ontario M5G 1M1, Canada*
[7] *QuSoft and CWI, Amsterdam, the Netherlands*

arXiv:1811.02149v1 [quant-ph] 6 Nov 2018

A fully homomorphic encryption system hides data from unauthorized parties, while still allowing them to perform computations on the encrypted data. Aside from the straightforward benefit of allowing users to delegate computations to a more powerful server without revealing their inputs, a fully homomorphic cryptosystem can be used as a building block in the construction of a number of cryptographic functionalities. Designing such a scheme remained an open problem until 2009, decades after the idea was first conceived, and the past few years have seen the generalization of this functionality to the world of quantum machines. Quantum schemes prior to the one implemented here were able to replicate *some* features in particular use-cases often associated with homomorphic encryption but lacked other crucial properties, for example, relying on continual interaction to perform a computation or leaking information about the encrypted data. We present the first experimental realisation of a quantum fully homomorphic encryption scheme. We further present a toy two-party secure computation task enabled by our scheme. Finally, as part of our implementation, we also demonstrate a post-selective two-qubit linear optical controlled-phase gate with a much higher post-selection success probability (1/2) when compared to alternate implementations, e.g. with post-selective controlled-Z or controlled-X gates (1/9).

I. INTRODUCTION

In 1978, Rivest, Adleman, and Dertouzos first imagined constructing a cryptosystem with the property that a party *without* a valid secret key required for decryption can nevertheless correctly evaluate a function f directly on a ciphertext x, without learning anything about either $f(x)$ or x [1]. In addition to the obvious benefit of being able to delegate computation to a party that is otherwise not trusted with private data, cryptographers have observed that elegant cryptographic solutions to particularly interesting tasks can be constructed on top of a fully homomorphic encryption scheme–secure multiparty computation, non-interactive zero-knowledge proofs, one-time programs, to name a few [2–6]. Despite the apparent utility of such an encryption scheme, the question of whether it was possible to efficiently construct one remained open until 2009 when the first fully homomorphic encryption (FHE) scheme was constructed for classical machines [7].

In quantum computing, a range of works have addressed the closely related problem of secure delegated computing [8–15] wherein Alice (whose quantum computer may be of limited power) can implement a quantum computation with the help of Bob (who possesses a more powerful quantum computer), without revealing her computation (or equivalently, her input). In these secure delegated quantum computing schemes, interaction between Alice and Bob can occur repeatedly as they collaborate to perform the desired computation. By contrast, in a fully homomorphic setting Bob is allowed to apply any quantum computation of his choice without further assistance from Alice. A secure delegated computing scheme therefore is not amenable to the wider gamut of cryptographic uses that a true FHE scheme should be, even if they are similar in spirit insofar as both allow delegation of computation on private data.

The question of quantum fully homomorphic encryption was studied more recently. The first proposals treated the problem in an information-theoretic security setting, where QFHE was subsequently shown to be impossible unless severe compromises to universality or security were made [16]. Schemes that were proposed under this model [17, 18], and subsequently demonstrated experimentally [19], leaked parts of the input and therefore do not satisfy mainstream notions of cryptographic security. Under standard cryptographic security, analogous to classical FHE where security necessarily requires computational assumptions, two QFHE schemes were theoretically proposed for tasks with a limited number of T

* Corresponding author.
wtham@physics.utoronto.ca