


Bounding quantum-classical separations for classes of nonlocal games

Tom Bannink[*] bannink@cwi.nl

Jop Briët[*†] j.briet@cwi.nl

Harry Buhrman[*‡] buhrman@cwi.nl

Farrokh Labib[*] labib@cwi.nl

Troy Lee[§] troyjlee@gmail.com

arXiv:1811.11068v1 [quant-ph] 27 Nov 2018

Abstract

We bound separations between the entangled and classical values for several classes of nonlocal t-player games. Our motivating question is whether there is a family of t-player XOR games for which the entangled bias is 1 but for which the classical bias goes down to 0, for fixed t. Answering this question would have important consequences in the study of multiparty communication complexity, as a positive answer would imply an unbounded separation between randomized communication complexity with and without entanglement. Our contribution to answering the question is identifying several general classes of games for which the classical bias can not go to zero when the entangled bias stays above a constant threshold. This rules out the possibility of using these games to answer our motivating question. A previously studied set of XOR games, known not to give a positive answer to the question, are those for which there is a quantum strategy that attains value 1 using a so-called Schmidt state. We generalize this class to mod-m games and show that their classical value is always at least $\frac{1}{m} + \frac{m-1}{m} t^{1-t}$. Secondly, for free XOR games, in which the input distribution is of product form, we show $\beta(G) \geq \beta^*(G)^{2^t}$ where $\beta(G)$ and $\beta^*(G)$ are the classical and entangled biases of the game respectively. We also introduce so-called line games, an example of which is a slight modification of the Magic Square game, and show that they can not give a positive answer to the question either. Finally we look at two-player unique games and show that if the entangled value is $1 - \varepsilon$ then the classical value is at least $1 - \mathcal{O}(\sqrt{\varepsilon \log k})$ where k is the number of outputs in the game. Our proofs use semidefinite-programming techniques, the Gowers inverse theorem and hypergraph norms.

[*]CWI, QuSoft, Science Park 123, 1098 XG Amsterdam, Netherlands.

Supported by the Gravitation-grant NETWORKS-024.002.003 from the Netherlands Organisation for Scientific Research (NWO).

[†]Additionally supported by a VENI grant.

[‡]University of Amsterdam.

Additionally supported by NWO Gravitation grant QSC, also supported by EU grant QuantAlgo.

[§]Centre for Quantum Software and Information, School of Software, Faculty of Engineering and Information Technology, University of Technology Sydney, Australia.

Part of this work was done while at the School for Physical and Mathematical Sciences, Nanyang Technological University and the Centre for Quantum Technologies, Singapore, supported by the Singapore National Research Foundation under NRF RF Award No. NRF-NRFF2013-13.