

2017–
2021

Weak approximate unitary designs and applications to quantum encryption

Cécilia Lancien[1] and Christian Majenz[2]

[1]Institut de Mathématiques de Toulouse & CNRS, Université Paul Sabatier, 118 route de Narbonne, F-31062 Toulouse Cedex 9, France.

[2]QuSoft and Centrum Wiskunde & Informatica, Science Park 123, 1098 XG Amsterdam, the Netherlands.

August 25 2020

arXiv:1911.06742v2 [quant-ph] 25 Aug 2020

Unitary t-designs are the bread and butter of quantum information theory and beyond. An important issue in practice is that of efficiently constructing good approximations of such unitary t-designs. Building on results by Aubrun (Comm. Math. Phys. 2009), we prove that sampling $d^t\mathrm{poly}(t, \log d, 1/\epsilon)$ unitaries from an exact t-design provides with positive probability an ϵ-approximate t-design, if the error is measured in one-to-one norm. As an application, we give a randomized construction of a quantum encryption scheme that has roughly the same key size and security as the quantum one-time pad, but possesses the additional property of being non-malleable against adversaries without quantum side information.

1 Introduction

Random unitaries, drawn from the Haar measure on the unitary group, play an important role in many aspects of theoretical quantum information science. For instance, most results on quantum source and channel coding are obtained with Haar-random coding strategies [ADHW09; HHWY08; BCR11] using the decoupling technique [HOW07; SDTR13; DBWR14; MBDRC17]. The columns and rows of Haar random unitaries are Haar random unit vectors and have also found many applications in quantum information theory, e.g. for constructing quantum money schemes [JLS18; AMR19]. However Haar random unitaries are infeasible to even approximate, the randomness and number of gates necessary to sample and implement them being exponential in the number of qubits they act on.

In most situations, unitary t-designs, the quantum analogues of t-wise independent functions, come to the rescue [DCEL09]. A unitary t-design is a measure on the unitary group that reproduces the Haar measure up to the t-th moment. This means that a random unitary sampled from a t-design can replace a Haar-random unitary in any situation where it is only applied t times. For practical purposes, one would like this measure to be more economical than the Haar measure (for instance to have finite, as small as possible, support). Often even just approximate versions of unitary t-designs (in the right metrics) are sufficient. In quantum information theory and related fields the most common metric between measures on the unitary group is the completely bounded one-to-one norm, or

Cécilia Lancien: clancien@math.univ-toulouse.fr
Christian Majenz: christian.majenz@cwi.nl