


Matchgate benchmarking: Scalable benchmarking of a continuous family of many-qubit gates

Jonas Helsen[1,2], Sepehr Nezami[3], Matthew Reagor[4], and Michael Walter[1,5,6]

[1]QuSoft & Korteweg-de Vries Institute for Mathematics, University of Amsterdam, Science Park 123, 1098 XG Amsterdam, The Netherlands
[2]Centrum Wiskunde & Informatica (CWI), Science Park 123, 1098 XG Amsterdam, The Netherlands
[3]Institute for Quantum Information and Matter, Caltech, Pasadena, CA 91125, USA
[4]Rigetti Computing, 775 Heinz Ave, Berkeley, CA 94710, USA
[5]Institute for Theoretical Physics & ILLC, University of Amsterdam, Science Park 123, 1098 XG Amsterdam, The Netherlands
[6]Faculty of Computer Science, Ruhr University Bochum, Universitätsstraße 150, 44801 Bochum, Germany

arXiv:2011.13048v2 [quant-ph] 15 Feb 2022

We propose a method to reliably and efficiently extract the fidelity of many-qubit quantum circuits composed of continuously parametrized two-qubit gates called matchgates. This method, which we call *matchgate benchmarking*, relies on advanced techniques from randomized benchmarking as well as insights from the representation theory of matchgate circuits. We argue the formal correctness and scalability of the protocol, and moreover deploy it to estimate the performance of matchgate circuits generated by two-qubit XY spin interactions on a quantum processor.

Quantum computers promise a revolution in computational power, and a multinational effort is underway to construct them. One of the key challenges in the building and operating of quantum computers is the appearance of errors in computations, either due to inaccuracies in control or due to interactions with the environment. It is thus vitally important to be able to characterize accurately and efficiently the type and magnitude of errors present in quantum operations. To this end, a variety of techniques have been developed, with the most popular class of techniques known as randomized benchmarking (RB) [1–9], where one characterizes the quality of gates in a gateset by applying random sequences of gates of increasing length, and tracks the corresponding increase in average error. For a recent overview of RB protocols see [10] and references therein.

Randomized benchmarking has been extremely successful in characterizing quantum operations on a variety of platforms [6, 11, 12]. Yet it suffers from a number of shortcomings that limit its usefulness in some important situations. Firstly, standard RB protocols mix the error contributions of various types of gates (such as single qubit gates and two qubit gates) and only report an average error. This is problematic because different types of gates are created by different physical mechanisms and hence have different error contributions. Moreover, different types of gates contribute differently to the error thresholds that must be met for fault-tolerance. For instance it is often the case that more stringent requirements are imposed on two-qubit gates than on single-qubit gates. Secondly, standard randomized benchmarking protocols only test discrete gatesets (such as the Clifford group), while continuously parametrized gatesets are vital for near-term quantum computing applications such as VQE and QAOA [13, 14]. For these reasons it is desirable to devise gate assessment procedures that combine the proven advantages of randomized benchmarking with the ability to handle continuous gate families and focus on a single type of quantum gates.

In this paper, we address this challenge by proposing *matchgate benchmarking*, an advanced randomized benchmarking procedure based on the general framework given in [10] as well as the recently introduced linear cross-entropy benchmarking [15]. Our procedure natively uses continuously parametrized two-qubit gates and estimates fidelities in a scalable way, both in terms of statistical sampling and classical computational resources. To prove its correctness and scalability we use techniques from the representation theory of the matchgate group. Moreover we provide an implementation of the protocol on a small quantum computer, showing that our protocol can reliably assess the quality of two qubit gates in a realistic environment.

Because this paper presents both proposals for experimental procedures and mathematical results, and thus is aimed at both experimental practitioners and theorists, we defer all technical proofs to appendices.

1 Matchgates

Matchgate circuits are a continuous class of quantum circuits originally conceived by Valiant [16] and sub-