


arXiv:2104.06814v1 [physics.atom-ph] 14 Apr 2021

A steady-state magneto-optical trap of fermionic strontium on a narrow-line transition

Rodrigo González Escudero,[1] Chun-Chia Chen (陳俊嘉),[1] Shayne Bennetts,[1] Benjamin Pasquiou,[1] and Florian Schreck[1,2,*]

[1] *Van der Waals-Zeeman Institute, Institute of Physics, University of Amsterdam, Science Park 904, 1098XH Amsterdam, The Netherlands*
[2] *QuSoft, Science Park 123, 1098XG Amsterdam, The Netherlands*

(Dated: April 15, 2021)

A steady-state magneto-optical trap (MOT) of fermionic strontium atoms operating on the 7.5 kHz-wide $^1S_0 - {}^3P_1$ transition is demonstrated. This MOT features 8.4×10^7 atoms, a loading rate of 1.3×10^7 atoms/s, and an average temperature of 12 µK. These parameters make it well suited to serve as a source of atoms for continuous-wave superradiant lasers operating on strontium's mHz-wide clock transition. Such lasers have only been demonstrated using pulsed Sr sources, limiting their range of applications. Our MOT makes an important step toward continuous operation of these devices, paving the way for continuous-wave active optical clocks.

I. INTRODUCTION

Optical atomic clocks [1] are proving to be powerful tools to answer fundamental questions in physics. They enable searches for dark matter [2–4], the study of gravitational waves [5], tests of general relativity [6, 7] or variations in nature's fundamental constants [8–10]. In the applied domain they are playing an increasingly important role in geology and geodesy [11–14].

Typically, state-of-the-art optical clocks operate in a time-sequential manner, with distinct phases for sample preparation and measurement. This mode of operation introduces aliasing of high-frequency noise, known as the Dick effect [15], which limits their performance [16]. To address this issue, several approaches have been followed: employing high-precision non-destructive detection techniques [17], developing novel experimental architectures to achieve high duty cycles [18] or interleaving the clock interrogations between two different atomic samples [19–21].

A new class of optical clocks based on the principle of superradiant lasing have been proposed as next-generation devices [22, 23]. Their working principle is inherently suited to continuous operation, thus circumventing the Dick effect. Furthermore, their potential goes beyond addressing this challenge: in the future they could outperform conventional clocks in terms of stability, detection bandwidth, and, by relaxing the requirements on external high-finesse cavities, portability and robustness [23, 24].

Pulsed superradiant lasing has already been demonstrated [25], in particular using strontium's $^1S_0 - {}^3P_0$ clock transition [26, 27]. There are ongoing efforts to incorporate steady-state atomic sources with this new type of clock [25, 28–30]. While there exist several strontium sources achieving the required flux and temperature [31, 32], all of these operate using bosonic isotopes, due to their simpler atomic structure. However, superradiant lasing using the clock line of bosonic strontium has, so far, not been demonstrated.

For bosonic strontium, the clock linewidth is orders of magnitude smaller than for its fermionic counterpart, and requires high external magnetic fields for the linewidth to be broadened enough for clock interrogation [33, 34]. Moreover, such fields must feature an exceptional degree of homogeneity and stability across the atomic sample for all atoms to participate in superradiant lasing [35]. Conversely, the laser cooling stages that are necessary to achieve the desired temperature and density operate best at low magnetic fields and gradients. These two adverse requirements complicate the integration of a steady-state source of bosonic strontium into an active optical clock. By contrast, a fermionic source seems better suited. Indeed, due to the non-zero nuclear magnetic moment of fermionic strontium, the clock transition naturally opens [1, 36], making it accessible without the need for high external magnetic fields.

Here we demonstrate a continuously loaded magneto-optical trap (MOT) of ultracold fermionic ^{87}Sr atoms, operated on the 7.5 kHz-wide $^1S_0 - {}^3P_1$ intercombination line. This narrow-line MOT features $8.41(4) \times 10^7$ atoms at an average temperature of 12.0(1) µK, is loaded with a rate of $1.31(2) \times 10^7$ atoms/s and reaches a peak density of $2.12(4) \times 10^9$ ^{87}Sr/cm^3. This steady-state source could be used to provide the high flux of ultracold atoms necessary to refill the gain medium of a steady-state superradiant active clock [24–26].

This article is structured as follows. Section II briefly describes the experimental setup necessary to produce a continuous MOT of strontium using the $^1S_0 - {}^3P_1$ transition, while Sec. III, IV, and V focus on the specificities pertaining to the fermionic isotope ^{87}Sr. Section III describes a 2D molasses, making use of the sawtooth-wave adiabatic passage (SWAP) technique to collimate an atomic beam passing from one chamber to the next. Section IV describes a narrow-line Zeeman slower adapted to fermionic strontium, thanks to optical

* FermiMOT@strontiumBEC.com