arXiv:2107.10551v2 [quant-ph] 4 Feb 2022

Stabilizer rank and higher-order Fourier analysis

Farrokh Labib

CWI, QuSoft, Science Park 123, 1098 XG Amsterdam, Netherlands. Supported by the Gravitation-grant NETWORKS-024.002.003 from the Dutch Research Council (NWO).

We establish a link between stabilizer states, stabilizer rank and higher-order Fourier analysis—a still-developing area of mathematics that grew out of Gowers's celebrated Fourier-analytic proof of Szemerédi's theorem [10]. We observe that n-qudit stabilizer states are so-called *nonclassical quadratic phase functions* (defined on affine subspaces of $\mathbb{F}_p^n$ where p is the dimension of the qudit) which are fundamental objects in higher-order Fourier analysis. This allows us to import tools from this theory to analyze the stabilizer rank of quantum states. Quite recently, in [20] it was shown that the n-qubit magic state has stabilizer rank $\Omega(n)$. Here we show that the qudit analogue of the n-qubit magic state has stabilizer rank $\Omega(n)$, generalizing their result to qudits of any prime dimension. Our proof techniques use explicitly tools from higher-order Fourier analysis. We believe this example motivates the further exploration of applications of higher-order Fourier analysis in quantum information theory.

1 Introduction

The Gottesman-Knill Theorem [9, 18] states that any quantum circuit consisting of Clifford gates can be efficiently classically simulated. The Clifford group on n qubits is generated by the Hadamard gate H, the $\pi/4$ phase gate S and the entangling CNOT gate. In particular, this means that circuits consisting only of Clifford gates cannot provide computational advantage over classical computers. We can promote such circuits to universal quantum computers by having access to a non-Clifford gate or (equivalently) a "magic state" [3]. It is widely believed that universal quantum computers cannot be efficiently simulated by classical computers: state-of-the-art simulators using modern day supercomputers are only able to simulate a few dozens of qubits [6, 12, 19, 22]. So it has to be this magic state that fuels the computational hardness of simulation by classical computers. It is therefore important to understand how much this resource costs in terms of free (efficiently simulatable) resources. These costs are quantified by "measures of magic" [16] an example of which is *stabilizer rank*, first introduced in [4]. Here, the free resources are states obtained from the canonical all-zero state by applying only Clifford operations, which are the well-known stabilizer states. To increase our understanding of non-stabilizerness, or the amount of "magic" a quantum state has, a valid approach might be to find a different characterization of these objects. This might introduce new techniques in analyzing measures of magic. It is well known that stabilizer states are quadratic forms defined on affine subspaces [7, 11, 14]. Here we observe that these objects are so-called *nonclassical quadratic phase functions* defined on affine subspaces which are well-studied objects in

Farrokh Labib: farrokhlabib@gmail.com