
2019–
2021


2019–
2021

Quantum Motif Clustering

Chris Cade, Farrokh Labib, and Ido Niesen

QuSoft & CWI, Amsterdam, the Netherlands.

arXiv:2111.13222v2 [quant-ph] 23 Jun 2023

We present three quantum algorithms for clustering graphs based on higher-order patterns, known as motif clustering. One uses a straightforward application of Grover search, the other two make use of quantum approximate counting, and all of them obtain square-root like speedups over the fastest classical algorithms in various settings. In order to use approximate counting in the context of clustering, we show that for general weighted graphs the performance of spectral clustering is mostly left unchanged by the presence of constant (relative) errors on the edge weights. Finally, we extend the original analysis of motif clustering in order to better understand the role of multiple 'anchor nodes' in motifs and the types of relationships that this method of clustering can and cannot capture.

1 Introduction

The study of complex networks has impacted many fields of science [Str01], including biology [Alb05, SOMMA02], sociology [WF94], neuroscience [BS17], and finance [AOTS15, GK10]. In particular, it is commonplace to study the connectivity patterns of networks at the edge and vertex level in order to uncover important structures in the underlying data. One method that provides insight into the connectivity structure of a network is graph clustering, which entails finding groups of highly connected vertices in order to uncover underlying community structures. There are many efficient (heuristic) algorithms for graph clustering, including the theoretically well-motivated *k-means spectral clustering*[1]. Here, given an integer k, the eigenvectors corresponding to the smallest k eigenvalues of the graph Laplacian are used as a feature set for a k-means clustering algorithm. It has been shown that in certain circumstances spectral clustering leads to the discovery of *optimal* graph partitions [PSZ15].

Recently, it is becoming popular to study more sophisticated connectivity patterns. This can be done in the context of, for example, hypergraphs[2] that can express multiple-vertex relationships, or via small subgraphs, also known as *motifs*, which can be used to study higher-order connectivity patterns between vertices. The latter has become a useful tool for providing deeper insight into a network's function and structure, although often the detection of these motifs remains computationally challenging [MNSK12].

In [BGL16], Benson et al. propose an algorithm for clustering a graph based on its *motif connectivity*. Their algorithm, which makes use of spectral clustering and therefore comes

[1] See [vL07] for a historical overview and list of references.

[2] www.quantamagazine.org/how-big-data-carried-graph-theory-into-new-dimensions-20210819/