


2017–
2021



Efficient NIZKs and Signatures from Commit-and-Open Protocols in the QROM

Jelle Don[1], Serge Fehr[1,2], Christian Majenz[3], and Christian Schaffner[4,5]

[1] Centrum Wiskunde & Informatica (CWI), Amsterdam, Netherlands
[2] Mathematical Institute, Leiden University, Netherlands
[3] Cyber Security Section, Department of Applied Mathematics and Computer Science, Technical University of Denmark, Kgs. Lyngby, Denmark
[4] Informatics Institute, University of Amsterdam, Amsterdam, Netherlands
[5] QuSoft, Amsterdam, Netherlands
jelle.don@cwi.nl, serge.fehr@cwi.nl, chmaj@dtu.dk, c.schaffner@uva.nl

arXiv:2202.13730v1 [cs.CR] 28 Feb 2022

Abstract. Commit-and-open Σ-protocols are a popular class of protocols for constructing non-interactive zero-knowledge arguments and digital-signature schemes via the Fiat-Shamir transformation. Instantiated with hash-based commitments, the resulting non-interactive schemes enjoy tight online-extractability in the random oracle model. Online extractability improves the tightness of security proofs for the resulting digital-signature schemes by avoiding lossy rewinding or forking-lemma based extraction.

In this work, we prove tight online extractability in the quantum random oracle model (QROM), showing that the construction supports post-quantum security. First, we consider the default case where committing is done by element-wise hashing. In a second part, we extend our result to Merkle-tree based commitments. Our results yield a significant improvement of the provable post-quantum security of the digital-signature scheme Picnic.

Our analysis makes use of a recent framework by Chung et al. [CFHL21] for analysing quantum algorithms in the QROM using purely classical reasoning. Therefore, our results can to a large extent be understood and verified without prior knowledge of quantum information science.

1 Introduction

Some interactive proofs come with amazing properties like *zero-knowledge* which intuitively allows a prover to convince a verifier that she knows the witness to an NP-statement without giving away any information about this witness. Such zero-knowledge proofs of knowledge are some of the most fascinating objects in cryptography, and possibly in all of theoretical computer science. One might suspect that their "magic" is rooted in the fact that the prover and verifier run an *interactive* protocol with each other, and that this interaction causes the verifier to be convinced. Surprisingly, if the interactive proof is of suitable form, e.g. a Σ-protocol (i.e. a 3-round public-coin protocol), the Fiat-Shamir transformation [FS87] provides a natural way to remove the interaction from such protocols while preserving (most of) the security properties, resulting in *non-interactive zero-knowledge* proofs (NIZKs). The idea is to compute the challenge c as a hash $c = H(a)$ of the first message, rather than letting the verifier choose c. If the original Σ-protocol has additional soundness properties, the resulting NIZK after the Fiat-Shamir transformation is ideally suited to be turned into a *digital-signature scheme*, simply by hashing the message m to be signed together with the first message a in order to obtain the challenge c. The candidates Picnic [CDG+17] and Dilithium [DKL+18] in the ongoing NIST post-quantum cryptography competition follow this design paradigm.

This intuitive preservation of security properties under the Fiat-Shamir transformation can be formalized in the random-oracle model (ROM), where the hash function H is treated as a uniformly random function, and the security reduction gets *enhanced access* to anybody who queries the random oracle, by seeing which values are queried, and by possibly returning (random-looking) outputs. While this situation is conveniently easy to handle in a non-quantum world, complications arise in the context of post-quantum security. When studying the security of these non-quantum protocols against attackers equipped with large-enough quantum computers, it is natural to assume that such attackers have access to the public description of the employed hash function, and can therefore compute it in superposition on their quantum computers. Therefore, the proper notion of post-quantum security for random oracles