

2021–
2026

Grothendieck inequalities characterize converses to the polynomial method

Jop Briët[1], Francisco Escudero Gutiérrez[1], and Sander Gribling[2]

[1]CWI & QuSoft, Science Park 123, 1098 XG Amsterdam, The Netherlands
[2]Tilburg University, Warandelaan 2, 5037 AB Tilburg, The Netherlands

arXiv:2212.08559v3 [quant-ph] 12 Nov 2024

A surprising 'converse to the polynomial method' of Aaronson et al. (CCC'16) shows that any bounded quadratic polynomial can be computed exactly in expectation by a 1-query algorithm up to a universal multiplicative factor related to the famous Grothendieck constant. Here we show that such a result does not generalize to quartic polynomials and 2-query algorithms, even when we allow for additive approximations. We also show that the additive approximation implied by their result is tight for bounded bilinear forms, which gives a new characterization of the Grothendieck constant in terms of 1-query quantum algorithms. Along the way we provide reformulations of the completely bounded norm of a form, and its dual norm.

1 Introduction

Quantum query complexity is one of the few models of computation in which the strengths and weaknesses of quantum computers can be rigorously studied with currently-available techniques (see e.g., [Amb18, Aar21] for recent surveys). On the one hand, many of quantum computing's best-known algorithms, such as for unstructured search [Gro96], period finding (the core of Shor's algorithm for integer factoring) [Sho97] and element distinctness [Amb07], are most naturally described in the query model. On the other hand, the model admits powerful lower-bound techniques.

For a (possibly partial) Boolean function $f : D \to \{-1, 1\}$ defined on a set $D \subseteq \{-1, 1\}^n$, the celebrated *polynomial method* of Beals, Buhrman, Cleve, Mosca and de Wolf [BBC+01] gives a lower bound on the quantum query complexity of f, denoted $Q(f)$, in terms of the minimal degree of an approximating polynomial for f, or approximate degree, $\widetilde{\deg}(f)$. The method relies on the basic fact that for any t-query quantum algorithm $\mathcal{A}$ that takes an n-bit

Jop Briët: j.briet@cwi.nl
Francisco Escudero Gutiérrez: feg@cwi.nl
Sander Gribling: s.j.gribling@tilburguniversity.edu,

This version extends arXiv version 1 of this work with most of [BE22], which appeared in the proceedings of TQC'22. This research was supported by the European Union's Horizon 2020 research and innovation programme under the Marie Skłodowska-Curie grant agreement no. 945045, and by the NWO Gravitation project NETWORKS under grant no. 024.002.003.