

2021–
2025

arXiv:2306.05385v1 [quant-ph] 8 Jun 2023

Line-graph qubit routing: from kagome to heavy-hex and more

Joris Kattemölle[1] and Seenivasan Hariharan[2,3]

[1] *Department of Physics, University of Konstanz, Konstanz, Germany*
[2] *Institute of Physics, University of Amsterdam, Amsterdam, The Netherlands*
[3] *QuSoft, CWI, Amsterdam, The Netherlands*

Quantum computers have the potential to outperform classical computers, but are currently limited in their capabilities. One such limitation is the restricted connectivity between qubits, as captured by the hardware's coupling graph. This limitation poses a challenge for running algorithms that require a coupling graph different from what the hardware can provide. To overcome this challenge and fully utilize the hardware, efficient qubit routing strategies are necessary. In this paper, we introduce line-graph qubit routing, a general method for routing qubits when the algorithm's coupling graph is a line graph and the hardware coupling graph is a heavy graph. Line-graph qubit routing is fast, deterministic, and effective; it requires a classical computational cost that scales at most quadratically with the number of gates in the original circuit, while producing a circuit with a SWAP overhead of at most two times the number of two-qubit gates in the original circuit. We implement line-graph qubit routing and demonstrate its effectiveness in mapping quantum circuits on kagome, checkerboard, and shuriken lattices to hardware with heavy-hex, heavy-square, and heavy-square-octagon coupling graphs, respectively. Benchmarking shows the ability of line-graph qubit routing to outperform established general-purpose methods, both in the required classical wall-clock time and in the quality of the solution that is found. Line-graph qubit routing has direct applications in the quantum simulation of lattice-based models and aids the exploration of the capabilities of near-term quantum hardware.

I. INTRODUCTION

Quantum computing offers potential to revolutionize a wide range of domains by efficiently solving problems that are intractable for classical computers [1, 2]. To run any quantum algorithm, it must be compiled into a quantum circuit that can be executed on the quantum hardware. The hardware coupling graph of a quantum computer, which defines adjacency between qubits based on the ability to perform two-qubit gates between them, plays a crucial role in this process. The problem of ensuring that a quantum circuit is compatible with the hardware coupling graph is referred to as the qubit routing problem [3, 4]. While generalized methods exist for qubit routing [5], a standard approach to implement two-qubit gates between non-adjacent qubits is to insert SWAP gates, making the qubits effectively adjacent [3, 4, 6–9]. To obtain a practical quantum advantage on noisy intermediate-scale quantum (NISQ) [10] devices, it is imperative that overhead arising from compilation is kept to a minimum [11, 12]. However, finding the swapping strategy that requires the least number of SWAP gates is NP-hard [3, 6], making it a challenging problem to solve. Heuristic, probabilistic methods have been developed, but their classical runtime may become problematic for large circuits, and the solution they find may be far from optimal [4, 7–9]. Striking the right balance between the classical resources required for routing and minimizing the circuit depth of the routed quantum circuit is crucial in maximizing the performance of NISQ devices.

The qubit routing problem is particularly evident in the quantum simulation of lattice-based spin models. One of the first areas in which it was realized that quantum computers could outperform classical computers was that of quantum simulation [13]. When applied specifically to lattice-based spin systems with two-body interactions, quantum simulation by Trotterization [14] approximates the overall time evolution operator of the quantum-mechanical system by a sequence of two-qubit gates, where each two-qubit gate corresponds to the time evolution according to one two-body term in the Hamiltonian (dynamic quantum simulation) [15, 16]. Additionally, by introducing variable parameters for the per-term evolution times, these circuits are transformed to circuits that prepare ansatz states for the variational quantum eigensolver (VQE) [17], designed to variationally find the ground state of the quantum-mechanical system (static quantum simulation). Before any routing, these circuits for dynamic and static quantum simulation naturally require hardware with a coupling graph that is equal to the lattice of the lattice-based spin system (the virtual graph) [17]. There will generally be a mismatch between the virtual graph and the hardware coupling graph. Efficient qubit routing plays a crucial role in overcoming this mismatch.

In this paper, we develop an efficient and deterministic qubit routing strategy, which we call line-graph qubit routing, or line-graph routing for short. It maps any circuit on a line graph $L(G)$ to hardware with coupling graph heavy(G). Here, heavy(G) is obtained from the graph G by placing a node on every edge of G. We call these added nodes the heavy nodes of heavy(G). By definition, the nodes of the line graph $L(G)$ consist of the heavy nodes of heavy(G). In $L(G)$, two nodes are adjacent if the associated edges in G are incident on the same