

# Composing Quantum Algorithms

Stacey Jeffery*
QuSoft, CWI & University of Amsterdam

arXiv:2502.09240v1 [quant-ph] 13 Feb 2025

**Abstract**

Composition is something we take for granted in classical algorithms design, and in particular, we take it as a basic axiom that composing "efficient" algorithms should result in an "efficient" algorithm – even using this intuition to justify our definition of "efficient." Composing quantum algorithms is a much more subtle affair than composing classical algorithms. It has long been known that zero-error quantum algorithms *do not* compose, but it turns out that, using the right algorithmic lens, bounded-error quantum algorithms do. In fact, in the bounded-error setting, quantum algorithms can even avoid the log factor needed in composing bounded-error randomized algorithms that comes from amplifying the success probability via majority voting. In this article, aimed at a general computer science audience, we try to give some intuition for these results: why composing quantum algorithms is tricky, particularly in the zero-error setting, but why it nonetheless works *better* than classical composition in the bounded-error setting.

## 1 Introduction

Algorithms designers and programmers make ubiquitous use of subroutines. Not only does this allow code to be easily reused, perhaps even in subroutine libraries used across platforms, it adds structure to a program, or algorithm, that makes the whole thing easier to analyze. For algorithms designers, the most important reason to use subroutines is probably that by black-boxing the algorithms designed by your ingenious colleagues, you can use them as building blocks within your own new algorithms.

Composition is a fundamental idea in complexity theory as well. One of the motivations for using polynomials as the class of growth functions considered "efficient" is that we feel intuitively that whenever we compose "efficient" algorithms, the resulting algorithm should also be "efficient" [AB09]. Perhaps one reason we take for granted that this should be true is the ease with which we can compose and analyze classical algorithms. If an algorithm $\mathcal{A}$ makes $Q$ queries to a subroutine $\mathcal{B}$ with time complexity $T(\mathcal{B})$, and $L$ additional operations, then its complexity is:

$$T(\mathcal{A}) = Q \cdot T(\mathcal{B}) + L,$$

as any first-year computer science student could tell you. This allows us to say things about the complexity of *composed* functions. Let $f : \{0,1\}^n \to \{0,1\}$ be the *composed function* $f = g \circ h$, where $g : \{0,1\}^m \to \{0,1\}$ for some $m = m(n) \leq n$, and $h : \{0,1\}^{n/m} \to \{0,1\}$, defined on $x \in \{0,1\}^n$ by

$$f(x) = f(x^{(1)}, \ldots, x^{(m)}) = g(h(x^{(1)}), \ldots, h(x^{(m)})),$$

where each $x^{(i)}$ is a $n/m$-bit string. Let $\mathbf{D}(f)$ be the *deterministic query complexity* of $f$, also called the *decision tree complexity*, which is the minimum number of queries to the bits of the input needed to decide $f$ (on the worst-case input). Then we can immediately see that

$$\mathbf{D}(g \circ h) \leq \mathbf{D}(g) \cdot \mathbf{D}(h),$$

*jeffery@cwi.nl. This article appears as the December 2024 Complexity Theory Column in SIGACT News [Jef24b].