



2022–
2024

ENTANGLEMENT RECYCLING IN TWO-STEP PORT-BASED TELEPORTATION

PIOTR KOPSZAK[1], DMITRY GRINKO[2,3,4], ADAM BURCHARDT[2,5], MARIS OZOLS[2,3,4], MICHAŁ STUDZIŃSKI[6], AND MAREK MOZRZYMAS [1]

Abstract. A protocol involving the repetitive (twofold, to be precise) application of PBT protocol to the same resource is studied. The quantities characterizing the resulting protocol, so-called *two-step PBT*, namely *enatnglement fidelity* and *success probability* are provided for two scenarios, relying on application of pretty-good measurement, i.e. deterministic and probabilistic PBT with non-EPR resource. This results show that two-step PBT is an accurate protocol, provided the resource is sufficiently large. In particular, the deterministic two-step PBT obtains fidelity that is remarkably close to the optimal MPBT fidelity for teleportation of two quantum states. Additionally, the *recycling fidelity*, i.e. the quantity characterizing the degradation of the resource state is calculated for repetitive application of probabilistic protocol, for both EPR and optimized resource, showing that entanglement recycling with two-step PBT is possible in the former case as well.

arXiv:2504.00710v3 [quant-ph] 8 Dec 2025

Contents

1. Introduction 1
2. Two-step PBT: description of the protocol 2
2.1. Quantifying the performance of two-step PBT 3
2.2. Degradation of the resource state in two-step probabilistic PBT 4
3. Summary of results 4
3.1. The quality of PGM-based two-step PBT 4
3.2. Resource degradation results 5
4. Mathematical preliminaries 5
4.1. Representation theory of the partially transposed permutation algebra 5
4.2. Optimal measurements and resource states for pPBT 6
5. Performance of the two-step PBT 8
5.1. Comparison with deterministic multi-PBT scheme 10
6. Degradation of the resource state in probabilistic port-based teleportation 11
6.1. Degradation of the resource state in standard pPBT 11
6.2. Degradation of the resource state for pPBT with optimised resource 13
7. Conclusions and open questions 15
Acknowledgements 15
Appendix A. Proof of Theorem 8 15
Appendix B. Proof of Theorem 9 17
References 19

1. Introduction

Quantum teleportation is one of the most remarkable applications of quantum entanglement, enabling the transmission of an unknown quantum state between two parties by employing only shared entanglement and classical communication [Ben+93]. Despite its wide range of applications, quantum teleportation has several limitations, such as the unitary correction step on receiver's side at the end of the protocol. This raises a natural question of whether this step can be avoided.

Port-based teleportation (PBT) introduced in 2008 by Hiroshima and Ishizaka [IH08; IH09] eliminates this problem. In this variant of quantum teleportation, the sender and receiver share a resource state composed of N maximally entangled EPR pairs called *ports*. The sender performs a joint quantum measurement on

[1] Institute for Theoretical Physics, University of Wrocław, Poland
[2] QuSoft, Amsterdam, The Netherlands
[3] Institute for Logic, Language, and Computation, University of Amsterdam, The Netherlands
[4] Korteweg-de Vries Institute for Mathematics, University of Amsterdam, The Netherlands
[5] Centrum Wiskunde & Informatica (CWI), Amsterdam, The Netherlands
[6] International Centre for Theory of Quantum Technologies (ICTQT), University of Gdańsk, Poland

E-mail addresses: piotr.kopszak2@uwr.edu.pl, d.grinko@uva.nl, adam.burchardt@cwi.nl, marozols@gmail.com, michal.studzinski@ug.edu.pl.