

2021–
2025

arXiv:2505.11986v2 [quant-ph] 1 Oct 2025

Peak state transfer in continuous quantum walks

Gabriel Coutinho[1], Krystal Guo[2,3], and Vincent Schmeits[2,3]

[1]Federal University of Minas Gerais, Belo Horizonte, Brazil
[2]Korteweg-de Vries Institute for Mathematics, University of Amsterdam, Amsterdam, The Netherlands
[3]QuSoft (Research center for quantum software & technology), Amsterdam, The Netherlands
gabriel@dcc.ufmg.br, k.guo@uva.nl, v.f.schmeits@uva.nl

May 17, 2025

Abstract

We introduce and study *peak state transfer*, a notion of high state transfer in qubit networks modeled by continuous-time quantum walks. Unlike perfect or pretty good state transfer, peak state transfer does not require fidelity arbitrarily close to 1, but crucially allows for an explicit determination of the time at which transfer occurs. We provide a spectral characterization of peak state transfer, which allows us to find many examples of peak state transfer, and we also establish tight lower bounds on fidelity and success probability. As a central example, we construct a family of weighted path graphs that admit peak state transfer over arbitrarily long distances with transfer probability approaching $\pi/4 \approx 0.78$, and we show how these are directly related to a family of unweighted graph which can also achieve peak state transfer after minor adjustments. Our analysis includes an explicit spectral characterization of these graphs which leads to the conclusion that these constructions offer improved robustness compared to classical perfect state transfer examples, such as the weighted paths derived from hypercubes, thereby identifying them as practical candidates for cheap and efficient quantum wires.

Keywords: state transfer, quantum walks, spectral graph theory, Hamiltonian dynamics, weighted graphs, quantum information
Mathematics Subject Classifications 2020: 81P45, 05C50, 05C90, 81Q99

1 Introduction

The ability to transmit quantum information with high fidelity is a fundamental requirement for quantum computing. One approach to achieving this is via a *quantum wire*: a network of interacting qubits that allows for a quantum state input at one of the qubits to be transferred to another site by means of the time-evolution of a Hamiltonian. This problem is not new; it has been studied in multiple works since the seminal paper [1], and several connections to the combinatorics of the network (a graph, from now on) have been found [3, 2, 16, 22, 5, 25, 9, 21, 24, 14]. This paper is motivated by the very natural goal of minimizing the size of the graph — with respect to both the number of qubits (vertices of the graph) and the number of interacting terms (edges of the graph) — while maintaining a large distance between the input and output qubits. In other words, we aim to build a cheap and long quantum wire.

Ideally, our quantum wire should transfer the input qubit state with probability 1 to the target qubit, and this indeed occurs in several known examples of graphs [6, 5]. This perfect state transfer is, however, not known to be available at arbitrary distances unless the size of the graph grows exponentially with the distance of the state transfer (see [3]), which is undesirable for practical applications. The most recent