

Getting almost all the bits from a quantum random access code

Han-Hsuan Lin* Ronald de Wolf†

June 11, 2025

arXiv:2506.01903v1 [quant-ph] 2 Jun 2025

Abstract

A quantum random access code (QRAC) is a map $x \mapsto \rho_x$ that encodes n-bit strings x into m-qubit quantum states ρ_x, in a way that allows us to recover any one bit of x with success probability $\geq p$. The measurement on ρ_x that is used to recover, say, x_1 may destroy all the information about the other bits; this is in fact what happens in the well-known QRAC that encodes $n = 2$ bits into $m = 1$ qubits. Does this generalize to large n, i.e., could there exist QRACs that are so "obfuscated" that one cannot get much more than one bit out of them? Here we show that this is not the case: for every QRAC there exists a measurement that (with high probability) recovers the full n-bit string x up to small Hamming distance, even for the worst-case x.

1 Introduction

1.1 Quantum Random Access Codes

Quantum states of m qubits are described by 2^m complex amplitudes, and it is tempting to try to use this exponential "space" to encode a lot of classical information in a quantum state. Holevo's theorem [Hol73] says that in general we cannot use this exponential space: if we encode some classical random variable X in an m-qubit quantum state ρ_X (via a map $x \mapsto \rho_x$), and then do a measurement on ρ_X to produce a classical random variable Y, then the mutual information between X and Y is at most m. So we cannot cram more than m bits of information into m qubits.

Quantum random access codes, first introduced in [ANTV99], address a more subtle situation where we demand less from the decoding: here $x \in \{0,1\}^n$ and we only want to be able to recover the bit x_i of x from ρ_x with success probability $p > 1/2$, for any $i \in [n]$ of our choice. Note that this is different from recovering *all* bits of x, since the measurement that recovers x_1 can change the m-qubit state, making it harder (or even impossible) to recover other bits of x. More formally:

Definition 1 *An (n, m, p)-quantum random access code (QRAC) is a map $x \mapsto \rho_x$ from the set of n-bit strings to the set of m-qubit mixed states, such that for each $i \in [n]$ there exists a 2-outcome POVM $\{M_0, M_1\}$ such that for each $x \in \{0,1\}^n$ and $b \in \{0,1\}$ we have $\mathrm{Tr}(M_b \rho_x) \geq p$ if $x_i = b$.*

*Department of Computer Science, National Tsing Hua University, Hsinchu 30013, Taiwan. Supported by NSTC QC project under Grant no. 111-2119-M-001-006-. linhh@cs.nthu.edu.tw

†QuSoft, CWI and University of Amsterdam, the Netherlands. Partially supported by the Dutch Research Council (NWO) through Gravitation-grant Quantum Software Consortium, 024.003.037. rdewolf@cwi.nl