

2022–
2024

Optimising quantum data hiding

Francesco Anna Mele[1,*] and Ludovico Lami[2,3,4,5,†]

[1]*NEST, Scuola Normale Superiore and Istituto Nanoscienze, Piazza dei Cavalieri 7, IT-56126 Pisa, Italy*
[2]*Scuola Normale Superiore, Piazza dei Cavalieri 7, 56126 Pisa, Italy*
[3]*QuSoft, Science Park 123, 1098 XG Amsterdam, The Netherlands*
[4]*Korteweg–de Vries Institute for Mathematics, University of Amsterdam, Science Park 105-107, 1098 XG Amsterdam, The Netherlands*
[5]*Institute for Theoretical Physics, University of Amsterdam, Science Park 904, 1098 XH Amsterdam, The Netherlands*

arXiv:2510.03538v1 [quant-ph] 3 Oct 2025

Quantum data hiding is the existence of pairs of bipartite quantum states that are (almost) perfectly distinguishable with global measurements, yet close to indistinguishable when only measurements implementable with local operations and classical communication are allowed. Remarkably, data hiding states can also be chosen to be separable, meaning that secrets can be hidden using no entanglement that are almost irretrievable without entanglement — this is sometimes called 'nonlocality without entanglement'. Essentially two families of data hiding states were known prior to this work: Werner states and random states. Hiding Werner states can be made either separable or globally *perfectly* orthogonal, but not both — separability comes at the price of orthogonality being only approximate. Random states can hide many more bits, but they are typically entangled and again only approximately orthogonal. In this paper, we present an explicit construction of novel group-symmetric data hiding states that are simultaneously separable, perfectly orthogonal, and even invariant under partial transpose, thus exhibiting the phenomenon of nonlocality without entanglement to the utmost extent. Our analysis leverages novel applications of numerical analysis tools to study convex optimisation problems in quantum information theory, potentially offering technical insights that extend beyond this work.

CONTENTS

I. Introduction 2

II. Problem statement 3

III. Construction of separable, orthogonal quantum data hiding states 4
A. Two special states 5
B. Bounding the LOCC norm via the PPT norm 9
C. Bounding the PPT norm 10
D. Concluding the proof 18

IV. Conclusions 18

V. Acknowledgements 19

References 19

A. $\mathcal{G}$-twirling 20

B. LOCC distinguishability of the two special states 21

* francesco.mele@sns.it
† ludovico.lami@gmail.com