



SpiderCat: Optimal Fault-Tolerant Cat State Preparation

Andrey Boris Khesin[1], Sarah Meng Li[2,3], Boldizsár Poór[1], Benjamin Rodatz[1], John van de Wetering[2,3], and Richie Yeung[1]

[1]University of Oxford, Oxford, United Kingdom
[2]University of Amsterdam, Amsterdam, Netherlands
[3]QuSoft, Amsterdam, Netherlands

arXiv:2603.05391v1 [quant-ph] 5 Mar 2026

The ability to fault-tolerantly prepare CAT states, also known as multi-qubit GHZ states, is an important primitive for quantum error correction. It is required for Shor-style syndrome extraction, and can also be used as a subroutine for doing fault-tolerant state preparation of CSS codewords. Existing approaches to fault-tolerant CAT state preparations have been found using computationally expensive heuristics involving SAT solving, reinforcement learning, or exhaustive analysis. In this paper, we constructively find optimal circuits for CAT states in a more scalable way. In particular, we derive formal lower bounds on the number of CNOT gates required for circuits implementing n-qubit CAT states that do not spread errors of weight at most t for $1 \leq t \leq 5$. We do this by using fault-equivalent rewrites of ZX-diagrams to reduce it to a problem of characterising certain 3-regular simple graphs. We then provide families of such optimal graphs for infinitely many values of n and $t \leq 5$. By encoding the construction of optimal graphs as a constraint satisfaction problem we find explicit constructions for circuits that match this lower bound on CNOT count for all $n \leq 50$ and $t \leq 5$ and for nearly all pairs (n, t) with $n \leq 100$ and $t \leq 5$ or $n \leq 50$ and $t \leq 7$, significantly extending the regimes that were achievable by previous methods and improving the resource counts for existing constructions. We additionally show how to trade CNOT count against depth, allowing us to construct constant-depth fault-tolerant implementations using $O(n)$ ancilla and $O(n)$ CNOT gates.

1 Introduction

As larger quantum computing devices become available, the first experimental demonstrations of fault-tolerant quantum computation have begun to emerge [1–3, 40, 49]. These results show that, by carefully structuring unitaries and measurements, it is possible to suppress the propagation of physical errors, detect faults as they occur, and actively correct them. While in the classical setting error correction is typically confined to communication and storage, while logical operations are assumed to be essentially noise-free, in quantum computing, however, every gate, measurement, and even idle qubit is inherently noisy [6, 14, 20]. As a result, fault tolerance must be treated as a global design constraint: the entire circuit architecture must be engineered so that errors remain controlled throughout the computation [19, 22, 36, 42].